

PU Plast – TECHNICAL DATA

Physical Properties

	PU Plast black 1 min.		PU Plast black 3,5 min.		PU Plast black 5 min.	
	Part A	Part B	Part A	Part B	Part A	Part B
Form	liquid	liquid	liquid	liquid	liquid	liquid
Colour	black	copper	black	copper	black	copper
Initial boiling point	> 200°C	> 300°C	> 200°C	> 300°C	> 200°C	> 300°C
Flash point	182°C	205°C	182°C	205°C	182°C	205°C
Vapour pressure	0,1 Pa	0,01 Pa	0,1 Pa	0,01 Pa	0,1 Pa	0,01 Pa
Relative density	1,0 g/cm ³	1,2 g/cm ³	1,0 g/cm ³	1,2 g/cm ³	1,0 g/cm ³	1,2 g/cm ³
Viscosity	3000 mPas	4000 mPas	3000 mPas	4000 mPas	3000 mPas	4000 mPas
Auto-ignition temperature	-	> 600°C	-	> 600°C	-	> 600°C

	PU Plast grey 1 min.	
	Part A	Part B
Form	liquid	liquid
Colour	grey	straw yellow
Initial boiling point	> 200°C	> 300°C
Flash point	182°C	205°C
Vapour pressure	0,1 Pa	0,01 Pa
Relative density	1,0 g/cm ³	1,2 g/cm ³
Viscosity	10000 mPas	3000 mPas
Auto-ignition temperature	-	> 600°C