

FTA

HIGH PERFORMANCE DUCT TAPE

- Strong initial tack
- Good adhesive power
- Extremely wear-resistant against abrasion
- Superb resistance to tape curl
- Due to high tack adhesive it adheres to a wide variety of substrates
- Easy to apply and hand tears in rectangular lines
- Moisture resistant and does not absorb water
- Easy to write on



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

FIX TAPE

GENERAL INFORMATION

FIX TAPE is a general purpose duct tape with strong initial tack and a good adhesive power. FIX TAPE is suitable for any adhesion on smooth or rough

surfaces such as stainless steel, glass, wood or polyethylene. FIX TAPE can be used for repairing and construction work, etc.

TECHNICAL INFORMATION


Adhesive: hot melt/synthetic rubber
 Base material (Carrier): PE coated fabric
 Colour: silver
 Odour: Slight rubber odour
 Specific gravity: 0,98 g/cm³
 Melting point: > 130°C
 Vapour resistance: Essentially non-volatile

Solubility in water (20°C): Negligible
 Adhesion to steel: 20 N / 25 mm
 Tensile strength: 75 N / 25 mm
 Thickness: 0,17 mm
 Temperature range: -10°C to +75°C (short term)
 Store clean and dry in a well ventilated area at a temperature between +10°C and +30°C.

APPLICATION AND USE

- **APPLICATION**
 Automotive, aerospace, military, general industrial, MRO, facilities management, transportation, marine, commercial vehicle, RV, bus, truck, ship yards, metal working, furniture, electronics, solar, trailer manufacturing and woodworking
 Lane marking, floor marking, safety coding, hazard marking, identifying, sealing, color coding, bundling, holding, reinforcing, identifying, tabbing, wrapping, splicing and protecting
- **USE**
 Temperature: between -5°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24h at +23°C

Article nr	Name	Content	Section
T581301	Fix Tape Silver 48mm x 50m	1 pc.	TAPES



TAPES

WWW.TECH-MASTERS.EU

