

# LTP-T

## EASY TO USE BLOWTORCH WITH SWIVEL BURNER FOR HANDS-FREE WORKS

- Automatic ignition - guaranteed for 30 000 ignitions
- Strong metal piezo cover for long lasting durability
- 360° swivel burner for hard to reach places
- Compact and stable cyclone flame
- Burner i high quality stainless steel
- Changeable and optional burners
- Valve body in brass with a protective nickel plating
- Built in regulator 0-3,5 bar
- Provides a temperature of 1925°C - 2400°C



# LOTPISTOLE TURBO

## GENERAL INFORMATION

For all kinds of brazing, soft soldering and heating applications. Available with piezo ignition.

## TECHNICAL INFORMATION

Working pressure: 0-3,5 bar  
 Burnerdiameter: 14  
 Gas consumption at 2 bar: 295  
 Effect: 3,8 kw

Soft soldering: 40 mm  
 Brazing max. 14 mm

## TECHNICAL INFORMATION CARTRIDGE AND BURNER

- Powergas 2203, 2204: Disposable cartridges 2203 and 2204 with self closing valve. Contains a gas mixture of 35% propane and 65% butane.
- Ultragas 2205: High efficient gas with built-in anti flare function . Disposable cartridges with self closing valve. Contains a gas mixture of propane, butane, propene and acetone. Weight: 450 g, Content: 336g / 600 ml.
- Ultramapp 2206: New unique gas mixture with increased flame temperature 2400°C. Disposable light weight aluminium cartridge with self closing valve. Environmental friendly, non-toxic gas mixture. Weight: 640 g, Content: 393 g/750 ml.
- Premium Quality propane 2208: Disposable light weight aluminium cartridge with self closing valve. Weight: 640 g, Content: 380 g/750 ml.
- Cyclon burner 2630: For all kinds of brazing, soft soldering and heating applications • Available with and without piezo ignition.  
 Burner diameter: 14mm  
 Gas consumption: 295g/h  
 Effect: 3,8kW  
 Soft soldering max diameter: 40mm  
 Brazing max diameter: 18mm.
- Turbo burner hot air 2632: For shrinking and paint stripping  
 Burner diameter: 38 mm  
 Gas consumption: 180g/h  
 Effect: 2,3 kW
- Twin cyclon burner 2633: For all kinds of brazing, soft soldering and heating applications. Twin construction for double speed.  
 Burner diameter Ø, mm 2x14  
 Gas consumption, g/h 590  
 Effect, kW 7,6  
 Soft soldering max Ø, mm 60  
 Brazing max Ø, mm 25

| Article nr | Name                          | Content | Section |
|------------|-------------------------------|---------|---------|
| Y902203    | Powergas 1925°C               | 300ml   | TOOLS   |
| Y902204    | Powergas 1925°C               | 600ml   | TOOLS   |
| Y902205    | Ultra Gas 2100°C              | 380ml   | TOOLS   |
| Y902206    | Ultramapp 2200°C              | 750 ml  | TOOLS   |
| Y902207    | Gas Ultra 2100° C             | 400 ml  | TOOLS   |
| Y902208    | Propanegas 1925°C             | 750ml   | TOOLS   |
| Y902630    | Cyclon Burner Turbojet        | 1 pc.   | TOOLS   |
| Y902632    | Turbo Hot Air Burner          | 1 pc.   | TOOLS   |
| Y902633    | Turbojet Cyclon Burner Double | 1 pc.   | TOOLS   |



## NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.