


## Automotive DIESEL HP

# ADD

### HIGH PERFORMANCE CLEANER FOR ALL DIESEL ENGINES

- Cleans diesel systems and combustion chambers
- Shown to reduce CO<sub>2</sub>-and HC emissions
- Cleans diesel systems and combustion chambers
- Keeps injection systems clean
- Saves fuel thanks to precise diesel savings and vapourisation
- Binds and neutralizes acid water and thus protects against corrosion
- Improves the lubricity of low-sulphur diesel fuel
- Improves starting behaviour and reduces knocking caused by diesel fuel



### General Information

DIESEL HP is a high performance additive for all diesel engine operating safety, reliability and economy. engines, that cleans diesel systems, improves diesel

### Technical Information


Physical state: liquid  
 Colour: yellow  
 Odour: characteristic  
 pH-Value (at 20°C): not determined DIN 19268  
 Initial boiling point: 100°C  
 Flash point: 62°C ISO 3679  
 Lower explosion limits: 0,5 vol. %

Upper explosion limits: 7,0 vol. %  
 Oxidizing properties: Not oxidizing.  
 Ignition temperature: 215°C  
 Density (at 20°C): 0,81 g/cm<sup>3</sup> DIN 51757  
 Water solubility: insoluble  
 Viscosity / kinematic (at 40°C):  
 2,11 mm<sup>2</sup>/s DIN EN ISO 3104

### Application and Use

- USING STRONG  
 Replace the fuel filter:  
 Pour in the filter part of the bottle DIESEL HP about 50 ml, add diesel to fill the filter and replace it. Pour the remaining approximately 250 ml product in the tank car.  
 Start up the engine for about 30-45 sec. Then turn off. Leave it off for at least 5 minutes so that the mixture concentrated (HP Diesel + fuel) injectors act more aggressively, to melt even the most tenacious deposits.  
 Start up the engine and run it until the regime has not been regularized.  
 If possible at this stage perceive a scheme and irregular beats of the engine.
- Add the contents of the tin to the tank. Fuel quantity up to 50 litres of DIESEL HP. The fuel quantity should at least equal the reserve volume.

Article nr	Name	Content	Section
T711001	Diesel HP	300ml	ADDITIVES
T711002	Diesel HP	5l	ADDITIVES



### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



ADDITIVES

WWW.TECH-MASTERS.EU

