

POL

DOUBLE SIDED TAPE FOR EASY AND IMMEDIATE MOUNTING

- · Extremely high ultimate adhesion.
- · Tearable by hand.
- Suited for high load bearing applications.
- Easy and immediate mounting of all kind of objects (e.g. nameplates, hooks, kitchen utensils, etc.)



POWER FIX LSE

General Information

POWER FIX LSE is a double sided tape which combines an excellent internal strength at elevated temperatures with a good tack and an extremely high ultimate adhesion to various

substrates. The polyester fabric provides strength and makes the tape tearable by hand.

POWER FIX LSE is very well suited for high load bearing applications to smooth and rough surfaces

Technical Information

Adhesive: Synthetic rubber Carrier: Polyester fabric, Semi transparent Liner: Polypropylene, Blue Thickness: 0,80 mm Adhesive strength, open side: 55 N/25 mm

Adhesive strength, covered side: 40 N/25 mm Tensile strength: 80 N/ 25 mm Static shear: 3kg at 23°C for > 168h Service temperature range: -10°C to +75°C Storage: Clean and dry in a well ventilated area, preferably at a temperature between $+15^{\circ}$ C and $+30^{\circ}$ C. Stored under these conditions shelf life will be a minimum of one year.

Chemical resistance: Limited UV resistance: Limited Ageing resistance: Good Plasticizer resistance: Limited Suitable for LSE: Yes

Application and Use

- Usage temperature should be between + 15°C and + 30°C.
- Surface must be clean and free from dust and grease.
- Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
- The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

Article nr	Name	Content	Section
T591019	Power Fix LSE	19mm x 10m	TAPES







Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



