

# LTP22

## THE LIGHT WEIGHT AND HAND HELD TORCH SYSTEM

- Automatic piezo ignition
- Trigger on/off function - no waste of LP gas
- Operates in all positions
- Wide range of quick changeable burners
- For disposable cartridges.
- Ergonomic light weight composite handle or sturdy heavy duty metal handle
- Provides a temperature of 2200° C



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# LOTPISTOLE ULTRAMAPP 2200

## GENERAL INFORMATION

Metaljet and Ultramapp gas form together the most powerful and efficient torch system on the market. A combination of modern combustion technology and unique gas mixture gives you a flame temperature of 2200°C.  
 Sturdy metal handle with

stainless steel high efficient cyclone burner 8707 for instant heat around the pipe. Heating, brazing and soldering works will be done with highest quality efficiency.

**PLEASE NOTE:**

Before using upside down, warm up 30 sec.

## TECHNICAL INFORMATION

Working pressure: 2 bar  
 For ultragas cartridge (not included): 2206  
 Can be used with all burners.

NO BURNER INCLUDED!

## TECHNICAL INFORMATION BURNER

- 8702: Pin-point burner for small soft soldering jobs. Gives a precise and stable flame  
 Burner diameter: 15mm  
 Gas consumption, at 2 bar: 40g/h  
 Effect, at 2 bar: 0,5kW  
 Soft soldering at 2 bar: 10mm
- 8704: Standard burner for soft soldering and other small heating jobs. For soft soldering and other small heating jobs.  
 Burner diameter: 16 mm  
 Gas consumption, at 2 bar: 90g/h  
 Effect, at 2 bar: 1,2kW  
 Soft soldering at 2 bar: 18mm
- 8706: Cyclone burner for brazing and soft soldering. Intensive and effective short flame that reaches around the pipe.  
 Burner diameter: 14 mm  
 Gas consumption, at 2 bar: 170g/h  
 Effect, at 2 bar: 2,2 kW  
 Soft soldering: 40 mm  
 Brazing at 2 bar: 18mm
- 8707: Cyclone burner for brazing and soft soldering. High efficient cyclone burner with increased tip diameter.  
 Burner diameter: 16 mm  
 Gas consumption, at 2 bar: 230g/h  
 Effect, at 2 bar: 2,9kW  
 Soft soldering: 40 mm  
 Brazing at 2 bar: 18mm
- 8708: Hot-air burner or shrinking and paint stripping. Powerful and wind stable hot-air stream.  
 Burner diameter: 38mm  
 Gas consumption, at 2 bar: 130g/h  
 Effect, at 2 bar: 1,7kW
- 8710: Soft flame burner or shrinking and heating jobs. Powerful and wind stable soft flame.  
 Burner diameter: 24 mm  
 Gas consumption, at 2 bar: 230g/h  
 Effect, at 2 bar: 3,5 kW  
 Soft soldering at 2 bar: 22 mm
- Copper bit: Made of copper with one pointed and one flat end. For use with burner 8702.

Article nr	Name	Content	Section
Y902155	Lotpistole Ultramapp 2200	1 pc.	TOOLS
Y902206	Ultramapp 2200°C	750 ml	TOOLS
Y908702	Pin-Point Burner	1 pc.	TOOLS
Y908704	Standard Burner	1 pc.	TOOLS
Y908706	Cyclon Burner	1 pc.	TOOLS
Y908708	Hot-Air Burner	1 pc.	TOOLS
Y908710	Soft Flame Burner	1 pc.	TOOLS
Y908843	Copper Bit	1 pc.	TOOLS
Y993257	Case (empty)	1 pc.	TOOLS



T908704

T908707

T908708

T908702

T908706

