

ULT

EXTRA HEAVY DUTY NON-MELT GREASE

- High Temperature Grease. Will stay in place at extremely high temperatures, in excess of 290°C.
- Clings to metal surfaces and coats them with an exclusive plating action.
- Withstand high pressures and heavy shock load.
- Strongly resists bleeding. Exclusive anti-wear additives provide exceptionally long lasting performance.
- Will not flush out by heavy rain. Provides complete, waterproof protection.
- Offers excellent protection against rust, corrosion, and wear.
- Is resistant to most acids, weather, salt spray, steam, oxidation and dirt.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

ULTIMATE GREASE

General Information

ULTIMATE GREASE is an extra heavy duty non-melt grease specially formulated from the highest quality paraffin base oils and special additives which enables it to withstand the

heavy impact and pounding pressures of equipment operating under boundary conditions without splattering. The grease stays in place without pounding out of the fitting or bearing.

Technical Information

Physical state: pasty
 Colour: Red
 Odour: characteristic
 Thickening agent: Bentonit (no mixing with other greases)
 Density (at 20 °C): 0,87g/cm³
 Initial boiling point and boiling range: 100 °C
 Flash point: >100° ISO 3679
 Water solubility: practically insoluble
 VKA: 3500 N
 Water Resistance: Excellent

Rust Resistance: Excellent
 Acid Resistance: Excellent.
 Conductivity: Non-Conductive
 NLGI Grade: 2.5
 Shelf life: 12 month, always keep the lid closed, store under shade away from direct heat.
 Safety measures: consult the Safety Data Sheet.
FOR PROFESSIONAL USE ONLY!

Application and Use

- ULTIMATE GREASE is recommended for use in: plain and anti-friction bearings, sleeve bearings, universal joints, water pumps, wheel bearings, drive shafts, spines, chains, chassis, 5th wheels, king pins and disc brakes.
- Reduces Downtime and maintenance labor because of smooth, cool performance.
- Outperforms and outlasts conventional greases in everyday lubrication functions. It is a lubricant formulated for the most severe operating conditions. Inventory is reduced with one superior quality, multi-purpose lubricant. Life of equipment is increased and maintenance costs reduced.

Article nr	Name	Content	Shelf Life	Catalog
T205001	Ultimate Grease	400g	see imprint + 24 months	LUBRICANTS
T205005	Ultimate Grease	5kg	see imprint + 24 months	LUBRICANTS
T205020	Ultimate Grease	20kg	see imprint + 24 months	LUBRICANTS

