

ACB

CONCENTRATED CLEANING AND DEGREASING AGENT

- High economic non-corrosive degreaser
- Applicable to all water resistant surfaces
- Effectively degreasing dry oily layers
- Especially suitable for preparing surfaces before applying paint and varnish
- Non-Corrosive to metals - contains a powerful corrosion inhibitor to reduce the hazard of corrosion to iron and steel.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

AQUA CLEAN BLUE

General Information

AQUA CLEAN BLUE is very economic noncorrosive degreaser useful for most water-resistant surfaces, where effectively removes dry oily layers, cutting and machining fluids, etc. It is especially suited for surface preparation before application of paints and varnishes. AQUA CLEAN BLUE effectively removes insects from windscreen and car body. On the greasy and oily layers

it acts as an emulsifier. Dirt in this process loses connection with the surface and incurred emulsion is removed by wiping or by rinsing. AQUA CLEAN BLUE can be diluted with water up to 1:20 for less demanding applications. It can be used near open flames, sparks and sources of heat.

Technical Information

Appearance: liquid
 Colour: light blue
 Odour: characteristic
 pH-value (at 20°C): 13,0 - 14,0
 Melting point: ≈ 0°C
 Freezing point: ≈ 0°C
 Initial boiling point: ≈ 100 °C

Flash point: 43°C
 Density (at 20°C): 1,03 g/cm³
 Water solubility: completely miscible
 Dynamic viscosity (at 25°C): < 10 mPas

Application and Use

- It is appropriate AQUA CLEAN BLUE applied to the cleaned surfaces by spraying, sprinkling, spreading or by using steam or pressure washing equipment. Efficiency when heated to 80 °C rises by up to 50%. We can therefore increase the ratio of water in working solution. Leave on for 30-60 seconds according to the structure of disposed dirt. Then rinse the surface and wipe dry.
 - **DILUTION TABLE**
- | | A | B | C | D |
|--------------------------|---|---|---|----|
| E | | | | |
| PARTS OF WATER | 1 | 2 | 5 | 10 |
| 20 | | | | |
| PARTS OF AQUA CLEAN BLUE | 1 | 1 | 1 | 1 |

- Surface Machine tools A-B
- Food machines B-C
- Floors D
- Brushing machines E
- Tarpaulins C-D
- Packaging machines E
- Steam cleaning E
- Metallurgical material A-B
- Circular saws B
- For cleaning of not very oily surfaces E

Article nr	Name	Content	Shelf Life	Catalog
T121005	Aqua Clean Blue	5l	see imprint + 36 months	CLEANERS AND DEGREASERS
T121010	Aqua Clean Blue	10l	see imprint + 36 months	CLEANERS AND DEGREASERS
T121025	Aqua Clean Blue	25l	see imprint + 36 months	CLEANERS AND DEGREASERS

