

# STO

## HEAVY DUTY CEMENT AND LIMESTONE REMOVER

- Removes Deposits Fast. STONE OFF instantly goes to work to remove heavy encrustations or mortar or scale.
- Safe to Tools and Equipment. STONE OFF will not harm metals normally found in tools or construction equipment. Do not use on magnesium, zinc (galvanized), or stainless steel.
- Penetrates. Special penetrants carry active ingredients in STONE OFF deep, thus reducing the time necessary to remove excess mortar and concrete.
- Easy to Apply. Spray or brush STONE OFF on surface to be cleaned, allow for thorough reaction, and rinse off.
- Rinses Freely. STONE OFF is water-soluble and completely rinses off leaving no residue.
- Inhibited. Special inhibitors will reduce attack on bare steel by 99,9% if rinsed thoroughly.



## NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# STONE OFF

## GENERAL INFORMATION

STONE OFF is a heavy duty, industrial concentrate cleaner for removing heavy mortar encrustations from cement trucks, cement mixers, wheel barrows,

metal equipment, shovels, brick, ceramic tile, transit forms etc. It is completely water soluble and leaves no residue.

## TECHNICAL INFORMATION

Type: Acidic detergent cleaner, renovator.  
 Flammability: Non-flammable  
 pH-Value (at 28° C): 0,5  
 Melting point: ca. 0° C  
 Initial boiling point and boiling range: ca 100° C  
 Density (at 25° C): 1,09 g/cm³

Water solubility: completely miscible  
 Viscosity / dynamic (at 25° C): < 10 mPa·s  
 Shelf life: 12 month,  
 Safety measures: consult the Safety Data Sheet.  
**FOR INDUSTRIAL AND COMMERCIAL USE ONLY!**

## APPLICATION AND USE

- Chip or scrape off excess accumulation of cement on outer surfaces. Use scrub pad, stiff brush, or coarse steel wool pad dipped in STONE OFF solution. Scrub surfaces thoroughly with the solution.
- Allow 3 to 5 minutes penetration and rinse off with clear water, repeat as necessary for heavy encrustations.
- For fresh, relatively light deposits, a solution of 1 part STONE OFF to 6 parts of water is sufficient.
- When tools are to be stored, spray on a light coating of MULTI TECH 6 for long lasting rust protection.
- **DO NOT USE ON MAGNESIUM, ZINC (GALVANIZED), OR STAINLESS STEEL.**

Article nr	Name	Content	Section
T111005	Stone Off	5l	CLEANERS AND DEGREASERS
T111010	Stone Off	10l	CLEANERS AND DEGREASERS
T111025	Stone Off	25l	CLEANERS AND DEGREASERS

