

SET-AC

HIGH-PERFORMANCE 1K ACRYLATE SEALANT

- Compatible with paints
- Free of solvents, isocyanate and silicone
- Adhesion to most common building substrates
- Easy tooling - wash-up with water



SEAL TECH AC

General Information

SEAL TECH AC is a plastoelastic one component acrylate sealant. It hardens as moisture evaporates. SEAL TECH AC can be used to seal joints and fill cracks

in interiors. It can be overpainted with all kinds of laquer and adheres to almost every surface. SEAL TECH AC is free from solvents, isocyanates and silicones.

Technical Information


Material: Thixotropic paste
 Type: Water based acrylic sealant
 Odour: None
 Consistency: Non-slump paste
 Specific gravity: Approx. 1.70 g/ml
 Skin forming time: Approx. 20 min. (at 23°C; 50% R.H.)
 Application temperature range: +5°C to +40°C

PROPERTIES OF THE CURED PRODUCT (at 23°C; 50% R.H.):
 Service temperature: -20°C to + 80°C
 Shore A Hardness (ISO 868): Approx. 30 (6mm thick film)
 Max. Tensile (ISO 37): Approx. 0.40 MPa
 Elongation at break (ISO 37): > 120 %

Application and Use

- **APPLICATION:**
 For sealing interior finishing joints for walls, partitions, ceiling and skirting boards.
 Connection joints on windowsills, between masonry, etc.
 For filling cracks, board joints, around shutter formwork, etc.
 Suitable for bonding expanded polystyrene on absorbent substrates.
 Suitable on all usual porous building substrates.
- **USE:**
 After substrate preparation, apply SEAL TECH AC with the TMT CAULKING GUN. The sealant should be smoothed using a tool moistened with water before skinning for a perfect sealant surface. Smoothing is not only recommended for aesthetic reasons, but also guarantees close contact and good adhesion to the substrate. Remove any masking tape used immediately after smoothing. Fresh product and tools can be cleaned with water.
 It should not be applied on bituminous or tar containing substrates, and to materials that bleed oils or plasticizers. It must not be used in contact with untreated metals (oxidation risk).

Article nr	Name	Content	Cection
T567101	Seal Tech AC white	290ml	ADHESIVES AND SEALANTS
T569000	TMT Caulking Gun 26:1	1 pc.	TOOLS
T569001	Nozzle 360°	6 pcs.	TOOLS
T569100	TMT Caulking Drill Adaptor	1pc.	TOOLS
T579001	Seal Tech Finisher	1l	ADHESIVES AND SEALANTS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

