

STC

ONE-COMPONENT CLEAR SEALANT

- Crystal clear sealant
- Non-yellowing - excellent resistance to UV
- Environmentally friendly
- Free of isocyanates and solvents - no hazard symbols
- No bubble formation
- Permanently flexible over a wide range of temperatures



SEAL TECH CRYSTAL

General Information

SEAL TECH CRYSTAL is one component, non-sagging, elastic SIMP (Silyl Modified Polymer) adhesive. It cures under the influence of atmospheric moisture to form a high performance, permanently flexible elastic sealant.

SEAL TECH CRYSTAL is solvent- and isocyanate free and has no VOC.

SEAL TECH CRYSTAL is odourless and does not form bubbles during and after application. It is perfectly resistant to UV rays and is non-yellowing.

Technical Information


Form: non-sag thixotropic paste
 Colour: crystal clear
 Chemical nature: SIMP - Silyl Modified Polymer
 Curing mechanism: moisture-curing
 Curing through volume (at 23°C and 50% RH): approx. 3,2mm
 Shore Hardness A (DIN 53505): approx. 44 N/mm²
 Relative density: 1,04 - 1,08 (ISO 1183-1 A)
 Tack-free time (at 23°C and 50% RH): approx. 35 min
 Elastic modulus at 100% (ISO 37 DIN 53504): approx. 1,4 N/mm²

Dynamic viscosity: 6000 - 95000 Pa*s (UNI EN ISO 3219 - Rotational viscometer)
 Tensile strength (ISO 37 DIN 53504): approx. 2,8 N/mm²
 Elongation (ISO 37 DIN 53504): approx. 230%
 Application temperature: -5°C - +40°C
 Temperature resistance: -40°C/+80°C, with brief point at +120°C
 Shelf life: 12 months in its original packaging (unopened)
 Storage: at 5°C - 25°C in a cool, dry place; keep away from wet areas, direct sunlight and heat sources

Application and Use

- APPLICATION:
 - Crystal clear sealing and bonding between different materials
 - Elastic bonding between metal, plastic, glass and other materials
 - Sealing joints in vertical and horizontal applications
 - High mechanical/dynamic stress resistance - shock/impact resistance
 - Increase torsional stiffness of final assembly
 - Vibration and sound damping bonding
 - Suitable for indoor and outdoor use
- USE:
 - Surface to be treated must be clean, dry and free from dust and grease
 - Primers may be required on some substrates and in certain application cycles
 - May be painted over (make a compatibility test beforehand)
 - Drying time of alkyd resin based paint may increase

Article nr	Name	Content	Shelf Life	Catalog
T569701	Seal Tech Crystal	290ml	see imprint + 12 months	ADHESIVES AND SEALANTS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

