

TRL

HIGH PERFORMANCE SPRAY-LUBE FOR ASSEMBLING AND DISASSEMBLING OF TIRES

- Reduces the friction resistance.
- Facilitates easy assembly and disassembly.
- No dirty grease smears are left on the tire.
- Does not attack aluminum, rubber or varnish/paint.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TIRE LUBE

General Information

TIRE LUBE is a high-performing lubricant for easy mounting and dismounting of rubber parts. TIRE LUBE is especially developed for fast assembling of tires on rims, particularly for low profile tyres and run flat tires. TIRE LUBE can also be used for pulling cables through

pipes and ducts or mounting of hoses, rubber plugs, door rubbers, rubber covers, silent blocs etc. TIRE LUBE does not attack aluminium, rubber or varnish/paint.

Technical Information

Form: aerosol
 Base: water, emulsifiers, preservatives, anti corrosion additives
 Propellant: propane - butane
 Odour: characteristic
 Boiling point: -44,5°C
 Flash point: -97°C
 Lower explosion limit: 0,6 Vol%
 Upper explosion limit: 10,9 Vol%
 Ignition temperature: > 200°C

Dynamic viscosity (at 20°C): 0 Pas
 Kinematic viscosity (at 40°C) : ≤ 20,5 mm²/s
 Organic solvents: 30%
 Pressure (at 20°C): 4 bar
 Spray rate (at 20°C): 1,5 g/sec
 Application temperature: 10 - 35°C
 Storage: cool (10°C - 20°C) and dry

Application and Use

- Use TIRE LUBE on room temperature and shake well before use.
- Before the application of TIRE LUBE clean the rubber parts with a degreaser such as FAST CLEAN or MEGA FOAM.
- For the best result, spray TIRE LUBE from a short distance on the rubber-parts and after a few minutes the solvents are evaporated and the items are ready for mounting and dismounting.

Article nr	Name	Content	Shelf Life	Catalog
T233981	Tire Lube	500ml	see imprint + 36 months	LUBRICANTS

