

WLB

WHITE LUBE 2600

WATER AND HEAT RESISTANT MULTIPURPOSE GREASE

- Multi-purpose grease with PTFE
- Reduces wear and friction of moving parts
- Long-lasting protection of bearing, axles, chains, hinges,...
- Excellent penetrating properties
- Water-resistant - cannot be rinsed away
- Prevents oxidation and corrosion
- Used for applications at temperatures between -20°C and 130°C
- Ideal for hard to reach areas

General Information

WHITE LUBE 2600 is a white multi purpose PTFE lubricant that consists of lithium soap and additives. Due to the special formulation WHITE LUBE 2600 is extremely resistant to heat and water, offering long-lasting protection of bearings, axles, chains, hinges and all moving parts. WHITE LUBE 2600 can be evenly applied with the included nozzle, even in hardly reachable areas. It effectively prevents corrosion and oxidation of the treated parts.

WHITE LUBE 2600 offers excellent penetrating properties making it the ideal product for applications such as lubrication of machinery and moving parts. The lube is a thin oil as first and changes to a grease texture.

Because of its texture WHITE LUBE 2600 cannot be rinsed away and is therefore perfect for every application where a continuous lubrication is needed.

Technical Information

Form: aerosol
 Appearance: white grease
 Base: lithium soap grease, additives
 Propellant: propane - butane
 Colour: white
 Odour: characteristic
 Boiling point: -44,5°C
 Lower explosion limit: 0,8 Vol%
 Upper explosion limit: 10,9 Vol%
 Flash point: -97°C
 Vapour pressure (at 20°C): 3300 hPa
 Pressure (at 20°C): 4 bar

Ignition temperature: > 200°C
 Organic solvents: 75%
 Solids content: 39,3 %
 Dropping point: 190°C
 NLGI classification: 2
 4 ball weld load (IP239): 260 kg
 Application temperature: 10°C - 35°C
 Spray pattern: jet, non dripping grease
 Shelf life: 12 months
 Storage: cool (10°C - 20°C) and dry
 Safety measures: consult the Safety Data Sheet

Application and Use

- APPLICATION:
 - For the lubrication of bearings, axles, chaings, hinges, window-slides, lock mechanisms, machine parts,...
 - Can be used on clutch and gas regulators, speedometer cables, gearings, pedals, ball-bearings, motorbike gears,...
 - Everywhere where the exposure to heat, water or dampness is frequent
 - For ventilators, gears, bearings, conveyor belts,....
- USE:
 - Use at room temperature (10°C-35°C)
 - Shake can well before use
 - Apply on the area/part to be treated
 - Let the solvent evaporate, takes approx. 5 min.
 - Remove excess lubricant with a cloth, avoid any residues

Article nr	Name	Content	Section
T231111	White Lube 2600	500ml	LUBRICANTS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



LUBRICANTS

WWW.TECH-MASTERS.EU

