

LIS

PROTECTS SURFACES FROM LIQUIDS AND DIRT

- Repels liquids and dirt
- Water resistant and breathable
- Does not change colour of fabrics and surfaces
- Prevents mold
- Expands shelf life
- Colourless
- Dirt does not tack on the surface



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

LIQUI STOP

General Information

LIQUI STOP is an impregnating spray used for the treatment of different kinds of textiles and soaking surfaces to make them resistant against different kinds of liquids and dirt. Due to its unique formula LIQUI STOP is covering and protecting every single molecule and fiber. It can safely be used on various material like textiles, canvas, fabrics and even leather.

LIQUI STOP gives the substrate excellent and long-lasting repellent properties against water and stains while keeping the natural characteristics such as colour, flexibility and breathability. LIQUI STOP is easy to apply and dries very fast making it ideal for an initial first protection.

Technical Information

Base: silicon resin, hydrocarbons, acetates
 Propellant: propane, butane
 Form: aerosol
 Colour: colourless
 Odour: characteristic
 Initial boiling point: -44,5°C
 Flash point: -97°C
 Ignition temperature: > 200°C
 Lower explosion limit: 0,6 Vol%
 Upper explosion limit: 10,9 Vol%

Vapour pressure (at 20°C): 3300 hPa
 Density (at 20°C): 0,649 g/cm³
 Water solubility: immiscible
 Kinematic viscosity (at 40°C): ≤ 20,5 mm²/s
 Application temperature: 10°C - 35°C
 Shelf life: 12 months
 Storage: cool (10°C - 20°C) and dry

Application and Use

- **USE:**
 - Use on room temperature.
 - Shake the can vigorously before use.
 - Test the spray on a small, inconspicuous area. Some dyes and materials may be sensitive to the used solvents. Do not use on rubber parts or plastic windows.
 - Spray on the surfaces to be treated from a distance of 20 - 25 cm.
 - Use LIQUI STOP outdoors or in a well ventilated place. Allow to dry for several hours before use.
 - Wash treated material only at temperatures beneath 30°C.
- **APPLICATION:**
 - For the treatment of all kinds of textiles, soaking surfaces, even leather and suede
 - Suitable for shoes, rain-coats, canvas, tents,...
 - Protects substrate from water, oil, coffee, tea, etc.

| Article nr | Name | Content | Shelf Life | Catalog |
|------------|------------|---------|-------------------------|----------------------------------|
| T155002 | Liqui Stop | 500ml | see imprint + 36 months | SURFACE PROTECTION AND TREATMENT |

