

PSL

POWERFUL AND RESILIENT RESTORATION TAPE

- Single sided tape with translucent acrylic film carrier
- Very high initial adhesion due to special formulation
- Flexible use any kind of surface
- Resistant against environmental impacts such as UV radiation, humidity and heat
- Ideal for water- and dustproof sealings
- Can be used for interior and exterior applications



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

POWER SEAL

General Information

For creating water- and dustproof sealings, POWER SEAL is your best choice. This single sided tape has an exclusively designed, translucent acrylic film as its carrier, making it very resilient with excellent restoration properties. In addition, the acrylic adhesive used in POWER SEAL has a very high initial adhesion which gives you a strong grip for a variety of applications.

Especially with environmental impacts such as UV radiation, humidity, water and heat, POWER SEAL will provide you ideal results in water- and dustproof sealings.

Due to the used flexible adhesive, contours, edges, rivets and screw heads can easily be covered for a tight seal. This makes it the perfect tape for all your interior and exterior applications.

Technical Information

Adhesive: acrylic adhesive
 Carrier: exclusive translucent acrylic film carrier
 Liner: transparent protective liner
 Thickness: 1,0 mm
 Adhesive strength: 100 N/25 mm
 Tensile strength: 37,5 N/25 mm
 Service temperature range: -40°C up to +80°C
 Elongation at break: 350%

UV-resistance: excellent
 Humidity resistance: excellent
 Storage: Clean and dry in a well ventilated area, preferably at a temperature between +21°C and +38°C
 Shelf life: min. 12 months, stored under these conditions mentioned above

Application and Use

- USE:
 - For best results, use the tape at temperatures between +15°C and +30°C.
 - Clean the surface to be treated. It must be free from dust and grease.
 - Apply the tape on the surface. Make sure that you do not touch the adhesive side.
 - Press down on the tape, especially on the sides and around unevenness such as screws, etc.
 - Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
 - Afterwards remove the protective film from the tape.
 - The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.
- APPLICATION:
 - Sealing for waterproof and dustproof application
 - Suitable for most surfaces
 - Gutters and downspouts
 - Vent stacks and windows
 - Outdoor lights and signs
 - Glass and metal enclosures
 - Leak patching and temporary repairs

Article nr	Name	Content	Shelf Life	Catalog
T490001	Power Seal	1,5m	-	TAPES



TAPES

WWW.TECH-MASTERS.EU

