

PTA

POWERFUL CABLE PROTECTION TAPE

- Prevents against wear, cracking, squeaking and vibrationsw
- Strong non-woven polyester fabric with synthetic rubber
- Easy application
- Suitable for the protection of a closed circuit
- Ideal for binding and protecting cables e.g. in cars, for sound systems,...
- Esthetical restoring of an original look
- Resistant against ageing
- Temperature resistance from -40°C to +105°C
- Suitable for repairing or tapping wire bundles, cable trees, pipes,...



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

PROTECT TAPE

General Information

PROTECT TAPE is a strong cable protection tape, especially developed for a solid and spiral taping of wire harness. PROTECT TAPE is easy to use thanks to its handy tearability and reduced unwinding force. This makes it ideal for mechanical applications. PROTECT TAPE is suitable for binding and protecting cables, for example in cars or for sound systems.

Due to the special composition, it has a very good temperature resistance and offers sound insulation. PROTECT TAPE is solvent-free, PVC-compatible and resistant against ageing and rotting. Thanks to the soft textile surface and very thin structure, PROTECT TAPE overlappings are almost invisible.





Technical Information

Adhesive: synthetic rubber
 Carrier: non-woven polyester fabric
 Colour: black
 Thickness: 0,30mm
 Length: 10m
 Adhesive strength: 10N / 25mm
 Tensile strength: 80N / 25mm
 Service temperature range: -40°C up to 105°C

Ageing resistance: good
 Elongation: 20%
 Adhesion to backing: 12,5N / 25mm
 Noise reducing: good
 Shelf life: 24 months
 Storage: clean and dry in a well ventilated area, preferably at a temperature between 5°C and 35°C.

Application and Use

- **USE:**
 - Use at a temperature between 10°C and 49°C.
 - Surfaces must be clean and free from dust and grease.
 - Avoid touching the exposed adhesive surface as this impairs the performance.
 - Pressure sensitive adhesive must be applied with a maximum of pressure to achieve maximum pressure level.
 - The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.
- **APPLICATION:**
 - Suitable for cables, wires, tube, pipes
 - Protects cables in dashboard or switch boxes against vibrations
 - Ideal for bundling cables
 - Protects repaired bundles and wires
 - Restore the original look

| Article nr | Name | Content | Section |
|------------|------|---|--|
| | |  |  |
| | |  | |
| | |  | |



TAPES

WWW.TECH-MASTERS.EU

