

## PWF

### PERMANENT BONDING TAPE FOR MULTI-PURPOSE USE

- 100% acrylic adhesive
- Provides high tack
- Suitable for various materials such as metal, wood, glass,...
- Excellent resistance to all external influences
- Can be used for interior and exterior applications



#### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## POWER FIX

### General Information

POWER FIX is especially designed for permanent bonding in interior and exterior applications. POWER FIX shows excellent resistance against humidity, UV-rays, chemicals and temperatures up to 90°C. POWER FIX can replace riveting, welding, liquid glues

and other permanent fasteners. POWER FIX has high tack properties and is suitable for various kinds of materials such as metal, wood, glass, plastics and many more.

### Technical Information

Thickness: 1,00 mm  
 Adhesive strength: 29 N/25 mm  
 Service temperature range: -40°C to +93°C  
 Short term temperature: +150°C  
 Solvent resistance: Good  
 Chemical resistance: Excellent  
 UV resistance: Excellent  
 Humidity resistance: Excellent

Dynamic shear: 5 kg/cm<sup>2</sup>  
 Static shear: 1000g/3,23cm<sup>2</sup> for 7 days at 23°C;  
 500g/3,23cm<sup>2</sup> for 7 days at 93°C  
 Storage: Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 24 months.

### Application and Use

- APPLICATIONS:
  - Fixing automotive exterior trims, bodyside moldings, rear view mirrors, ...
  - Signage industry (mounting of nameplates, emblems, logos, badges, panels, ...)
  - Electronic displays.
  - Mounting of decorative material and trims.
  - Fixing panel to frame and stiffener to panel.
  - Window and door assembly.
  - Interior and exterior use.
- RECOMMENDATIONS FOR USE:
  - The temperature should be between +15°C and +30°C. Before applying POWER FIX the surface must be clean and free from dust and grease. Therefore you can use MEGA FOAM or FAST CLEAN. POWER FIX must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

| Article nr | Name                 | Content | Section |
|------------|----------------------|---------|---------|
| T554120    | Power Fix 12mm x 10m | 1 pc.   | TAPES   |
| T554190    | Power Fix 19mm x 10m | 1 pc.   | TAPES   |



TAPES

WWW.TECH-MASTERS.EU

