

# ICF

## POWERFUL DEFROSTER

- Easy to apply
- Defrosting windows, doors and locks
- Act immediately
- Prevents the emergence of a new ice



# ICE FREE

## General Information

ICE FREE is a fast and powerful defroster glass, various types of locks, rubber seals etc.. Penetration into the lock at the same time repels moisture, leaving a thin, viscous film and thus delay

the subsequent freezing. Contains alcoholic solution, with the addition of agents preventing icing.

## Technical Information


Aerosol:  
 Form: aerosol  
 Colour: clear  
 Odour: alcoholic  
 Initial boiling point and boiling range: -42 °C  
 Flash point: -80°C  
 Upper/lower flammability or explosive limits: 1.7 – 28 Vol-%  
 Density (at 20°C): 0,843 g/cm<sup>3</sup>  
 VOC content: 80,42% or 280g/can  
 Contains organic propellant.

Liquid:  
 Appearance: clear liquid (20 °C)  
 Odour: alcoholic  
 Flash point: < 23 °C  
 Flammability (solid, gas): highly flammable liquid and vapour  
 Density at 20 °C: 0.8 - 0.805 g/cm<sup>3</sup>

## Application and Use

- Use to defrosting of carglass, doors, windows and locks.
- Protects and does not attack rubberseals.
- Protects against re-ice.
- Shake well and spray from a distance of 20-30 cm. Wait for de-icing.

Article nr	Name	Content	Shelf Life	Catalog
T132201	Ice Free	400ml	see imprint + 36 months	SURFACE PROTECTION AND TREATMENT
T132202	Ice Free	500ml	see imprint + 36 months	SURFACE PROTECTION AND TREATMENT



## Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

