

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 1/21



Rustcon Aerosol 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Rustcon Aerosol 500ml

Article No.:

T181001

UFI:

NK87-WUW4-HD0A-083A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Aerosol coating

1.3. Details of the supplier of the safety data sheet

Supplier:

Techniqua Handels GmbH

Hartleitnerstraße 3

4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: office@techniqua.at

Supplier:

TECH-MASTERS Austria GmbH

Kallham 7

4720 Kallham

Austria

Telephone: +43 7733 20090

Telefax: +43 7733 20092

E-mail: info@tech-masters.at

Website: www.tech-masters.eu/at

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 2/21



Rustcon Aerosol 500ml

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS05
Corrosion



GHS07
Exclamation mark



GHS08
Health hazard

Signal word: Danger

Hazard components for labelling:

Butan-1-ol; Reaction mass of ethylbenzene and xylene; Phenol, 4,4'-(1-methylethyidene)bis-polymer with 2,2'-[(1-methylethyidene)bis(4,1-phenylene oxymethylene)] bis[oxirane]; Acetone

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary statements Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Storage

P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

P501	Dispose of contents/container to an appropriate recycling or disposal facility.
------	---

2.3. Other hazards

Other adverse effects:

The product does not meet the PBT/vPvB criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 3/21

Rustcon Aerosol 500ml

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 115-10-6 EC No.: 204-065-8 REACH No.: 01-2119472128-37	dimethyl ether Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	25 - < 50 %
CAS No.: 67-64-1 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	Acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	10 - < 25 %
EC No.: 905-588-0 REACH No.: 01-2119488216-32	Reaction mass of ethylbenzene and xylene The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	10 - < 25 %
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	2.5 - < 10 %
CAS No.: 68648-78-2 EC No.: 614-691-7	Polyvinylbutyral The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	2.5 - < 10 %
CAS No.: 107-98-2 EC No.: 203-539-1 REACH No.: 01-2119457435-35	1-methoxypropan-2-ol Substance with a community workplace exposure limit.	2.5 - < 10 %
CAS No.: 71-36-3 EC No.: 200-751-6 Index No.: 603-004-00-6 REACH No.: 01-2119484630-38	Butan-1-ol Acute Tox. 4 (H302), Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) Danger	≥ 3 - < 10 %
CAS No.: 1401-55-4 EC No.: 215-753-2	Tannins Eye Irrit. 2 (H319) Warning	2.5 - < 10 %
CAS No.: 25036-25-3 EC No.: 607-500-3	Phenol, 4,4'-(1-methylethyldiene)bis-polymer with 2,2'- [(1-methylethyldiene)bis(4,1-phenylene oxymethylene)] bis[oxirane] Eye Irrit. 2 (H319), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Warning	1 - < 2.5 %
CAS No.: 78-83-1 EC No.: 201-148-0 Index No.: 603-108-00-1	2-methylpropan-1-ol Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) Danger	0.1 - < 1 %
CAS No.: 108-65-6 EC No.: 203-603-9 Index No.: 607-195-00-7 REACH No.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning	0.1 - < 1 %
CAS No.: 1330-20-7 EC No.: 215-535-7 Index No.: 601-022-00-9 REACH No.: 01-2119488216-32	Xylene Acute Tox. 4 (H332, H312), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger	0.1 - < 1 %

Full text of H- and EUH-phrases: see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 4/21



Rustcon Aerosol 500ml

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

After inhaling vapours, first symptoms of poisoning may develop hours later, so always consult a doctor.

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

Wash with plenty of soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 5/21



Rustcon Aerosol 500ml

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	① 1,000 ppm (1,910 mg/m ³)
MAK (AT)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	② 2,000 ppm (3,820 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	① 1,000 ppm (1,920 mg/m ³)
MAK (AT)	Acetone CAS No.: 67-64-1	② 2,000 ppm (4,800 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	Acetone CAS No.: 67-64-1	① 500 ppm (1,210 mg/m ³)
MAK (AT)	Acetone CAS No.: 67-64-1	① 500 ppm (1,200 mg/m ³)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m ³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m ³)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 6/21

Rustcon Aerosol 500ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	① 100 ppm (375 mg/m ³) ② 150 ppm (568 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	① 50 ppm (187 mg/m ³) ② 50 ppm (187 mg/m ³) ⑤ (Momentanwert, kann über die Haut aufgenommen werden) H
MAK (AT)	Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	① 50 ppm (150 mg/m ³)
MAK (AT)	Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	② 200 ppm (600 mg/m ³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	② 200 ppm (600 mg/m ³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	① 50 ppm (150 mg/m ³)
MAK (AT)	2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	② 100 ppm (550 mg/m ³) ⑤ (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden) H
IOELV (EU)	2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m ³) ② 100 ppm (550 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT)	2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H
MAK (AT) from 25 Sept 2018	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	② 100 ppm (442 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT) from 25 Sept 2018	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	1,894 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	471 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 7/21

Rustcon Aerosol 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
Acetone CAS No.: 67-64-1	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Acetone CAS No.: 67-64-1	200 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Acetone CAS No.: 67-64-1	2,420 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Acetone CAS No.: 67-64-1	186 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Acetone CAS No.: 67-64-1	62 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Acetone CAS No.: 67-64-1	62 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	77 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	14.8 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	289 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	180 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	108 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	1.6 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	369 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	43.9 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	553.5 mg/m ³	① DNEL worker ② Acute - inhalation, local effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 8/21

Rustcon Aerosol 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	50.6 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	18.1 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	3.3 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	2.7 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	0.5 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	214 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	159.8 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	310 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	55 mg/m ³	① DNEL Consumer ② Long-term - inhalation, local effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	5.5 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	2.7 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	0.3 mg/kg bw/day	① DNEL worker ② Long-term - oral, systemic effects
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6	3,125 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	275 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	796 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	320 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	36 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	221 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 9/21

Rustcon Aerosol 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	65.3 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	442 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	260 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	221 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	65.3 mg/m ³	① DNEL Consumer ② Long-term - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	442 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	260 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	212 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	125 mg/kg	① DNEL Consumer ② Long-term - dermal, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.5 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.155 mg/L	① PNEC aquatic, freshwater
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.016 mg/L	① PNEC aquatic, marine water
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.681 mg/kg	① PNEC sediment, freshwater
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.069 mg/kg	① PNEC sediment, marine water
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.045 mg/kg	① PNEC soil
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	1.549 mg/L	① PNEC aquatic, intermittent release
Acetone CAS No.: 67-64-1	10.6 mg/L	① PNEC aquatic, freshwater
Acetone CAS No.: 67-64-1	1.06 mg/L	① PNEC aquatic, marine water
Acetone CAS No.: 67-64-1	100 mg/L	① PNEC sewage treatment plant
Acetone CAS No.: 67-64-1	30.4 mg/L	① PNEC sediment, freshwater

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 10/21

Rustcon Aerosol 500ml

Substance name	PNEC Value	① PNEC type
Acetone CAS No.: 67-64-1	3.04 mg/L	① PNEC sediment, marine water
Acetone CAS No.: 67-64-1	29.5 mg/kg	① PNEC soil
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	0.327 mg/L	① PNEC aquatic, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	6.58 mg/L	① PNEC sewage treatment plant
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, freshwater
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	2.31 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	10 mg/L	① PNEC aquatic, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	1 mg/L	① PNEC aquatic, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC sewage treatment plant
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	52.3 mg/kg	① PNEC sediment, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	5.2 mg/kg	① PNEC sediment, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	4.49 mg/kg	① PNEC soil

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 11/21

Rustcon Aerosol 500ml

Substance name	PNEC Value	① PNEC type
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC aquatic, intermittent release
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.0635 mg/L	① PNEC aquatic, freshwater
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.0064 mg/L	① PNEC aquatic, marine water
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	100 mg/L	① PNEC sewage treatment plant
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	3.29 mg/L	① PNEC sediment, freshwater
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.329 mg/L	① PNEC sediment, marine water
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.29 mg/kg	① PNEC soil
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, freshwater
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, marine water
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.46 mg/kg	① PNEC sediment, freshwater
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.46 mg/kg	① PNEC sediment, marine water
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	2.31 mg/kg	① PNEC soil
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section: 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Wear gloves for protection against chemicals according to EN 374.

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 12/21

Rustcon Aerosol 500ml

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: $\geq 0,5\text{mm}$

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Filter A2/P2

Other protection measures:

General protective and hygienic measures:

Keep away from food, drink and animal feed.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol

Colour: light brown

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② Mixture is not polar/aprotic.
Initial boiling point and boiling range	-24.8 °C		
Flash point	-42 °C		
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	235 °C		
Upper/lower flammability or explosive limits	1.1 - 20 Vol-%		
Vapour pressure	5,200 hPa	20 °C	
Density	0.797 g/cm ³	20 °C	
Bulk density	<i>not applicable</i>		
Water solubility	<i>not applicable</i>		② Not miscible or only slightly miscible.
Kinematic viscosity	$\leq 20.5 \text{ mm}^2/\text{s}$	40 °C	

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 13/21



Rustcon Aerosol 500ml

9.2.1. Information with regard to physical hazard classes

Explosives:

Not applicable

Flammable gases:

Not applicable

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

Oxidizing gases:

Not applicable

Gases under pressure:

Not applicable

Flammable liquids:

Not applicable

Flammable solids:

Not applicable

Self-reactive substances and mixtures:

Not applicable

Pyrophoric liquids:

Not applicable

Pyrophoric solids:

Not applicable

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

Oxidizing liquids:

Not applicable

Oxidizing solids:

Not applicable

Organic peroxides:

Not applicable

Corrosive to metals:

Not applicable

Desensitised explosives:

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 14/21



Rustcon Aerosol 500ml

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8
LD₅₀ oral: >2,000 mg/kg
LD₅₀ dermal: >2,000 mg/kg
LC₅₀ Acute inhalation toxicity (dust/mist): 308.5 mg/L 4 h (Rat)
Acetone CAS No.: 67-64-1
LD₅₀ oral: ≥5,000 mg/kg (Rat)
LD₅₀ dermal: >20 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >50 mg/L 4 h (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat)
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0
LD₅₀ oral: >3,523 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): 27.571 ppmV 4 h (Rat)
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD₅₀ oral: >2,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L (Rat)
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
ATE (oral): 4,016 mg/kg
LD₅₀ oral: 4,016 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): 28.8 ppmV 4 h (Rat)
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6
LD₅₀ oral: 2,292 mg/kg (Ratte)
LD₅₀ dermal: 3,430 mg/kg (Kaninchen)
LC₅₀ Acute inhalation toxicity (gas): 21 ppmV 4 h (Ratte)
Tannins CAS No.: 1401-55-4 EC No.: 215-753-2
LD₅₀ oral: 2,260 mg/kg (Ratte)
LC₅₀ Acute inhalation toxicity (vapour): 2,260 mg/L
Phenol, 4,4'-(1-methylethyldene)bis-polymer with 2,2'-[(1-methylethyldene)bis(4,1-phenylene oxymethylene)] bis[oxirane] CAS No.: 25036-25-3 EC No.: 607-500-3
LD₅₀ oral: >2,000 mg/kg (Ratte)
LD₅₀ dermal: >2,000 mg/kg (Ratte)
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
LD₅₀ oral: >5,000 mg/kg (Mouse) OECD 401
LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402
LC₅₀ Acute inhalation toxicity (gas): >1,883 ppmV (Rat)
LC₅₀ Acute inhalation toxicity (vapour): 37 mg/L 4 h (Rat)
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7
LD₅₀ oral: 2,100 mg/kg (Rat)
LD₅₀ dermal: 1,100 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): >20 mg/L

Acute oral toxicity:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 15/21



Rustcon Aerosol 500ml

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8
LC ₅₀ : >4,000 mg/L 2 d (crustaceans, Daphnia magna)
LC ₅₀ : >4,000 mg/L 4 d (fish)
EC ₅₀ : 155 mg/L 4 d (Algae/water plant)
Acetone CAS No.: 67-64-1
LC ₅₀ : 8,300 mg/L 4 d
LC ₅₀ : 5,540 mg/L 4 d (fish, Oncorhynchus mykiss)
LC ₅₀ : 4,042 mg/L (fish)
EC ₅₀ : 8,800 mg/L 2 d (crustaceans, Daphnia magna)
EC ₅₀ : 8,300 mg/L (fish)
EC ₅₀ : 302 mg/L 4 d (Algae/water plant)
NOEC: 2,212 mg/L (crustaceans, Daphnia pulex)
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0
LC ₅₀ : 8.9 - 16.4 mg/L 4 d (fish, Pimephales promelas)
EC ₅₀ : 3.2 - 9.5 mg/L 2 d (crustaceans, Daphnia magna)
NOEC: 0.44 mg/L 3 d (Algae/water plant)
LC ₅₀ : 2.6 mg/L 4 d (fish, Oncorhynchus mykiss)
EC ₅₀ : 2.2 mg/L 3 d (Algae/water plant, Chlorella vulgaris)
NOEC: >1.39 mg/L (fish, Oncorhynchus kisutch)
NOEC: 0.74 mg/L (crustaceans, Ceriodaphnia dubia)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 16/21



Rustcon Aerosol 500ml

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LC₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas)
LC₅₀ : >1,000 mg/L 4 d (fish)
EC₅₀ : >100 mg/L (Algae/water plant)
EC₅₀ : >100 mg/L 2 d (crustaceans, Daphnia magna)
EC₅₀ : >1,000 mg/L 2 d (crustaceans)
ErC₅₀ : >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)
LOEC : 1,000 mg/L (Algae/water plant, Algae)
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
LC₅₀ : 6,812 mg/L 4 d (fish, Leuciscus idus)
EC₅₀ : 23,300 mg/L 2 d (crustaceans, Daphnia magna)
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6
LC₅₀ : 1,376 mg/L 4 d (fish, Pimephales promelas)
EC₅₀ : 225 mg/L (Algae/water plant, Selenastrum capricornatum)
EC₅₀ : 225 mg/L (Algae/water plant, Selenastrum capricornutum)
NOEC : 4.1 mg/L 21 d (crustaceans, Daphnia magna)
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
LC₅₀ : <180 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
LC₅₀ : 18 - 24 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
EC₅₀ : >400 mg/L 2 d (crustaceans, Daphnia magna)
EC₅₀ : 10 mg/L (Activated sludge) OECD 204
NOEC : 47.5 mg/L (fish, Oryzias latipes)
NOEC : 100 mg/L (crustaceans, Daphnia magna)
IC₅₀ : >25,000 mg/L 4 d (fish, Danio rerio (zebrafish))
ErC₅₀ : >85 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 203
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7
LC₅₀ : >10 - 100 mg/L 4 d (fish)
EC₅₀ : >10 - 100 mg/L 2 d (crustaceans)
EC₅₀ : >10 - 100 mg/L 3 d (Algae/water plant)
NOEC : 1.3 mg/L (fish, Oncorhynchus mykiss)
NOEC : 1.17 mg/L (crustaceans, Ceriodaphnia dubia)

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

Additional ecotoxicological information:

No further relevant information available.

12.2. Persistence and degradability

Acetone CAS No.: 67-64-1
Biodegradation: Yes, rapidly
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Biodegradation: Yes, rapidly
Remark: Readily biodegradable (according to OECD criteria).
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Biodegradation: Yes, rapidly
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 17/21



Rustcon Aerosol 500ml

12.3. Bioaccumulative potential

Acetone CAS No.: 67-64-1
Log K_{OW} : -0.23
Bioconcentration factor (BCF) : 3
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0
Log K_{OW} : 3.16
Bioconcentration factor (BCF) : 29
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Log K_{OW} : 0.05
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Log K_{OW} : -0.44
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
Log K_{OW} : 1.2

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8
Results of PBT and vPvB assessment: —
Acetone CAS No.: 67-64-1
Results of PBT and vPvB assessment: —
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0
Results of PBT and vPvB assessment: —
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Results of PBT and vPvB assessment: —
Polyvinylbutyral CAS No.: 68648-78-2 EC No.: 614-691-7
Results of PBT and vPvB assessment: —
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Results of PBT and vPvB assessment: —
Butan-1-ol CAS No.: 71-36-3 EC No.: 200-751-6
Results of PBT and vPvB assessment: —
Tannins CAS No.: 1401-55-4 EC No.: 215-753-2
Results of PBT and vPvB assessment: —
Phenol, 4,4'-(1-methylethylidene)bis-polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenylene oxymethylene)] bis[oxirane] CAS No.: 25036-25-3 EC No.: 607-500-3
Results of PBT and vPvB assessment: —
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
Results of PBT and vPvB assessment: —
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7
Results of PBT and vPvB assessment: —

The product does not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 18/21



Rustcon Aerosol 500ml

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV
Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant — skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste treatment options





Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Other disposal recommendations:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Attention: Gases	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Attention: Gases	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Attention: Gases	Special Provisions: A145 A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: Attention: Gases

14.7. Maritime transport in bulk according to IMO instruments

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 19/21



Rustcon Aerosol 500ml

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: Acetone

Regulation (EC) No 273/2004 on drug precursors: Acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: Acetone

Other regulations (EU):

Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

Named dangerous substances:

- Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 678.6 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1

Page 20/21



Rustcon Aerosol 500ml

LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Jan 2023

Print date: 21 Nov 2023

Version: 1



Page 21/21

Rustcon Aerosol 500ml

Hazard statements

H373	May cause damage to organs through prolonged or repeated exposure.
------	--

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

16.6. Training advice

No data available

16.7. Additional information

No data available