

## SCE

### POWERFUL SOLVENT DEGREASER

- N-hexane free.
- Leaves no residue of oily film.
- Softens and dissolves grease and oils.
- Removes dirt fast and efficiently.
- High spray delivery rate.
- Fast, thorough and safe degreasing and cleaning.
- Very economical.
- Removes adhesives, sealants, oil, grease, silicon, wax, tar, paraffin, printing ink, ....



### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## SAFE CLEAN ECO

### General Information

SAFE CLEAN ECO is an efficient solvent based cleaner and degreaser, used for removing all kinds of grease, oil, dirt and dust. Due to its special formulation SAFE CLEAN ECO softens and dissolves grease and oils thus leaving the treated surface residue-free.

SAFE CLEAN ECO dries very fast which makes it ideal for the use on brake discs, pads, cylinders, calipers and other machinery parts. In addition, SAFE CLEAN ECO is n-hexane free and therefore more eco-friendly.

### Technical Information

Form: aerosol  
 Colour: colourless  
 Odour: characteristic  
 Melting point: -60 °C  
 Initial boiling point and boiling range: 82°C  
 Upper/lower flammability or explosive limits: 0.7 - 7 Vol-%  
 Flash point: 6°C  
 Auto-ignition temperature: 256 °C  
 pH-value: mixture is non-polar/aprotic  
 Kinematic viscosity (at 40°C): 0,6 mm²/s

Dynamic viscosity (at 20°C): 0,76 mPas  
 Solubility in water (at 20°C): 0,1 g/l  
 Vapour pressure (at 20°C): 20 hPa  
 Density (at 20°C): ≈ 0,75 g/cm³  
 Organic solvents: 96,5%  
 Pressure (at 20°C): 5 - 5,5 bar  
 Kinematic viscosity (at 40°C): 0.6 mm²/s  
 Application temperature: 10 - 35°C  
 Storage: cool (10 - 20°C) and dry  
 Shelf life: 12 months

### Application and Use

- **USE:**
  - Use on room temperature and shake the can well before use.
  - Spray onto the surface/object to be cleaned.
  - In certain heavy cases, the product needs time to soak.
  - If necessary, wipe off with a clean cloth.
  - Leave the surface afterwards to evaporate/dry.
- **APPLICATION:**
  - SAFE CLEAN ECO is perfect for cleaning brake and clutch parts, such as brake discs, drums, pads, cylinders and calipers.
  - It removes adhesives, sealants, oil, grease, silicon, wax, tar, paraffin, printing ink, ....
  - It may damage paint and some plastics. Therefore, the product must always be tested in a concealed area first.

Article nr	Name	Content	Shelf Life	Catalog
T109005	Safe Clean Eco 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS

