

# FFP

## PRIMER FOR FAST FIX GLUES

- For the treatment of nonpopular surface (e.g. polyethylene, polypropylene, PTFE)
- Usable on a wide range of difficult surfaces
- Excellent strength



### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# FAST FIX PRIMER

## General Information

FAST FIX PRIMER is a solvent based primer for the treatment of nonpopular surfaces such as polyethylene, polypropylene or PTFE.

With FAST FIX PRIMER difficult surfaces can be bonded with any FAST FIX glue.

## Technical Information

Physical state: Aerosol  
 Colour: transparent  
 Odour: characteristic  
 Density (at 20°C): 0,7 g/cm³  
 Viscosity: < 20 mPas  
 Initial boiling point and boiling range: < 0 °C  
 Flash point: < 0 °C

Shelf life: 12 months at room temperature  
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
 Buildup of explosive mixtures possible without sufficient ventilation.

## Application and Use

- 1. Clean the surface thoroughly.
- 2. Fast Fix Primer should be applied to a clean, lint-free cloth / paper / sponge and the surface should be wetted with it.
- 3. ATTENTION: Before the adhesive is applied, the solvent must be completely evaporated!
- 4. ATTENTION: There should not be more than an hour between applying the primer and applying the adhesive.
- 5. ATTENTION: If only one part to be joined is made of non-polar plastic, only this must be treated with primer. In this case, the adhesive should be applied to the untreated surface.
- 6. Load the bond only after the final strength has been reached.

Article nr	Name	Content	Shelf Life	Catalog
T501014	Fast Fix Primer 50ml	50ml	see imprint + 36 months	ADHESIVES AND SEALANTS
T501015	Fast Fix Primer Liquid 10ml	10ml	see imprint + 15 months	ADHESIVES AND SEALANTS

