

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 1/14



## Copper Spray 500ml

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

Copper Spray 500ml

Article No.:

T114002

UFI:

N8M4-DSQE-QPHJ-9405

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricating agent

#### 1.3. Details of the supplier of the safety data sheet

Supplier:

**KANDO Service GmbH**

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

#### 1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols ( <i>Aerosol 1</i> )	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation ( <i>Skin Irrit. 2</i> )	H315: Causes skin irritation.	
Hazardous to the aquatic environment ( <i>Aquatic Chronic 1</i> )	H410: Very toxic to aquatic life with long lasting effects.	

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



**GHS02**  
Flame



**GHS07**  
Exclamation mark



**GHS09**  
Environment

Signal word: Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 2/14



## Copper Spray 500ml

### Hazard components for labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

#### Hazard statements for health hazards

H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

#### Hazard statements for environmental hazards

H410	Very toxic to aquatic life with long lasting effects.
------	---

#### Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing and eye protection/face protection.

#### Precautionary statements Response

P302 + P352	IF ON SKIN: Wash with plenty of water and soap.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER if you feel unwell.

#### Precautionary statements Storage

P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Precautionary statements Disposal

P501	Dispose of contents/container to an appropriate recycling or disposal facility.
------	---

### Additional information:

Formation of explosive mixtures possible without adequate ventilation.

### 2.3. Other hazards

#### Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Description:

Active ingredient mixture with propellant gas

#### Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 3/14

## Copper Spray 500ml

### Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 921-024-6 REACH No.: 01-2119475514-35	<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	25 - < 50 Vol-%
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	10 - < 25 Vol-%
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	<b>propane</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	10 - < 25 Vol-%
CAS No.: 7440-50-8 EC No.: 231-159-6 REACH No.: 01-2119480154-42	<b>copper</b> Acute Tox. 3 (H331), Acute Tox. 4 (H302), Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Eye Irrit. 2 (H319) Danger M-factor (acute): 1 M-factor (chronic): 10	2.5 - < 10 Vol-%
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	<b>Isobutane (with &lt; 0.1 % butadiene (203-450-8))</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	2.5 - < 10 Vol-%

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Following inhalation:

If unconscious, position and transport in stable lateral position.

#### In case of skin contact:

Wash off immediately with soap and water and rinse well.

#### After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

#### Following ingestion:

Do not induce vomiting, seek medical help immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

#### Unsuitable extinguishing media:

Water in full jet

### 5.2. Special hazards arising from the substance or mixture

No further relevant information available.

### 5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 2 Aug 2023

**Print date:** 19 Feb 2024

**Version:** 2

Page 4/14



## Copper Spray 500ml

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

**Personal precautions:**

Wear protective equipment. Keep unprotected persons away.

##### 6.1.2. For emergency responders

No data available

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

#### 6.3. Methods and material for containment and cleaning up

**Other information:**

Provide adequate ventilation.

#### 6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Protective measures**

**Advices on safe handling:**

Ensure good ventilation/extraction at the workplace.

**Fire prevent measures:**

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Requirements for storage rooms and vessels:**

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

**Hints on storage assembly:**

The official regulations for the storage of pressurised gas packages must be observed.

**Storage class (TRGS 510, Germany):** 2B - Aerosol dispensers and lighters

**Further information on storage conditions:**

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

#### 7.3. Specific end use(s)

**Recommendation:**

No further relevant information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 5/14

## Copper Spray 500ml

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m <sup>3</sup> )
MAK (AT)	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m <sup>3</sup> )
MAK (AT)	<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	① 1 mg/m <sup>3</sup> ② 4 mg/m <sup>3</sup> ⑤ (eintembare Fraktion, max. 4x15 min./Schicht)
MAK (AT)	<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	① 0.1 mg/m <sup>3</sup> ② 0.4 mg/m <sup>3</sup> ⑤ (alveolengängige Fraktion max. 4x15 min./Schicht)
MAK (AT)	<b>Isobutane (with &lt; 0.1 % butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht Momentanwert)
MAK (AT)	<b>Isobutane (with &lt; 0.1 % butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m <sup>3</sup> )

##### 8.1.2. Biological limit values

No data available

##### 8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	2,035 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	608 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	773 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	300 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 6/14

## Copper Spray 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	699 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6	699 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	20 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	20 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	1 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	1 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, local effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	137 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	137 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	273 mg/kg bw/day	① DNEL worker ② Acute - dermal, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	273 mg/kg bw/day	① DNEL Consumer ② Acute - dermal, systemic effects
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6	0.041 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No further details. See section 7.

### 8.2.2. Personal protection equipment



#### Eye/face protection:

Safety goggles (EN-166)

#### Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness:  $\geq 0,5$  mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 7/14



## Copper Spray 500ml

we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149 EN340&EN ISO 13688 EN13034-6).

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

### Other protection measures:

General protective and hygienic measures:

Keep away from food, drink and animal feed.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

General ventilation.

### 8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state:** Aerosol

**Colour:** According to product designation

**Odour:** characteristic

#### Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② Mixture is not polar/aprotic.
Melting point	-60 °C		
Initial boiling point and boiling range	-44.5 °C		
Flash point	-97 °C		
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	> 200 °C		
Upper/lower flammability or explosive limits	0.8 - 10.9 Vol-%		
Vapour pressure	3,800 hPa	20 °C	
Density	≈ 0.714 g/cm <sup>3</sup>	20 °C	
Bulk density	<i>not applicable</i>		
Water solubility	Immiscible		
Kinematic viscosity	20.5 mm <sup>2</sup> /s	40 °C	

### 9.2. Other information

The product is not self-igniting.

Organic solvents: 65,0%

Solid content: 34,7%

#### 9.2.1. Information with regard to physical hazard classes

##### Explosives:

Not applicable

##### Flammable gases:

Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 2 Aug 2023

**Print date:** 19 Feb 2024

**Version:** 2



Page 8/14

## Copper Spray 500ml

### **Aerosols:**

Extremely flammable aerosol. Pressurized container: May burst if heated.

### **Oxidizing gases:**

Not applicable

### **Gases under pressure:**

Not applicable

### **Flammable liquids:**

Not applicable

### **Flammable solids:**

Not applicable

### **Self-reactive substances and mixtures:**

Not applicable

### **Pyrophoric liquids:**

Not applicable

### **Pyrophoric solids:**

Not applicable

### **Self-heating substances and mixtures:**

Not applicable

### **Substances or mixtures which, in contact with water, emit flammable gases:**

Not applicable

### **Oxidizing liquids:**

Not applicable

### **Oxidizing solids:**

Not applicable

### **Organic peroxides:**

Not applicable

### **Corrosive to metals:**

Not applicable

### **Desensitised explosives:**

Not applicable

## SECTION 10: Stability and reactivity

### **10.1. Reactivity**

No further relevant information available.

### **10.2. Chemical stability**

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

### **10.3. Possibility of hazardous reactions**

No dangerous reactions known.

### **10.4. Conditions to avoid**

No further relevant information available.

### **10.5. Incompatible materials**

No further relevant information available.

### **10.6. Hazardous decomposition products**

No dangerous decomposition products known.

## SECTION 11: Toxicological information

### **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	EC No.: 921-024-6
---	-------------------

<b>LD<sub>50</sub> oral:</b> >5,000 mg/kg (Rat) OECD 401
--

<b>LD<sub>50</sub> dermal:</b> >2,920 mg/kg (Rabbit)
--

<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> >20 ppmV 4 h (Rat) OECD 403
---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 9/14



## Copper Spray 500ml

<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9
<b>LD<sub>50</sub> oral:</b> 5,840 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> 13,900 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> >25 ppmV 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> ≥50 mg/L 4 h (Rat)
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6
<b>LD<sub>50</sub> oral:</b> >2,000 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> 300 - 2,500 mg/kg (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 5.11 mg/L (Rat)

### Acute oral toxicity:

Based on available data, the classification criteria are not met.

### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

### Skin corrosion/irritation:

Causes skin irritation.

### Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

### STOT-single exposure:

May cause drowsiness or dizziness.

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### Endocrine disrupting properties:

None of the ingredients are included.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6
<b>LC<sub>50</sub>:</b> 11.4 mg/L 4 d (fish, <i>Oncorhynchus mykiss</i> ) OECD 203
<b>EC<sub>50</sub>:</b> 3 mg/L 2 d (crustaceans, <i>Daphnia magna</i> ) OECD 202
<b>NOEC:</b> 0.17 mg/L 21 d (crustaceans, <i>Daphnia magna</i> )
<b>LOEC:</b> 0.32 mg/L 21 d (crustaceans, <i>Daphnia magna</i> )
<b>EC<sub>50</sub>:</b> 30 - 100 mg/L 3 d (Algae/water plant, <i>Pseudokirchneriella subcapitata</i> )

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 10/14



## Copper Spray 500ml

<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9
<b>LC<sub>50</sub></b> : 9,640 mg/L 4 d (fish, Pimephales promelas)
<b>LC<sub>50</sub></b> : 0.41 mg/L 4 d (fish, Oncorhynchus mykiss)
<b>LC<sub>50</sub></b> : 49.9 mg/L 4 d (fish)
<b>EC<sub>50</sub></b> : >100 mg/L (Algae/water plant, Bacteria)
<b>EC<sub>50</sub></b> : 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum)
<b>EC<sub>50</sub></b> : 69.43 mg/L 2 d (crustaceans, Daphnia)
<b>NOEC</b> : 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
<b>ErC<sub>50</sub></b> : 19.37 mg/L 4 d (Algae/water plant)
<b>LOEC</b> : 1,000 mg/L (Algae/water plant, Algae)
<b>LOEC</b> : 1,000 mg/L (Algae/water plant, Alge)
<b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6
<b>LC<sub>50</sub></b> : 0.000072 mg/L 2 d (crustaceans, Krustazeen)
<b>LC<sub>50</sub></b> : 0.000072 mg/L 2 d (crustaceans, Krustazeen, Adultus)
<b>LC<sub>50</sub></b> : 0.000072 mg/L 2 d (crustaceans, Amphipoda)
<b>EC<sub>50</sub></b> : 0.0021 mg/L 2 d (crustaceans, Daphnia)
<b>NOEC</b> : 0.0008 mg/L (fish, Oreochromis niloticus)
<b>NOEC</b> : 0.0008 mg/L (crustaceans, Krustazeen)
<b>IC<sub>50</sub></b> : 0.016 mg/L 3 d (Algae/water plant, Chlorella pyrenoidosa)
<b>IC<sub>50</sub></b> : 0.016 mg/L 3 d (Algae/water plant, Chlorella pyrenoidosa)

### Aquatic toxicity:

No further relevant information available.

### Assessment/classification:

No further relevant information available.

## 12.2. Persistence and degradability

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6
<b>Biodegradation:</b> Yes, rapidly
<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9
<b>Biodegradation:</b> Yes, rapidly

### Biodegradation:

Not readily biodegradable.

## 12.3. Bioaccumulative potential

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6
<b>Log K<sub>OW</sub></b> : 5.2
<b>Bioconcentration factor (BCF):</b> 250
<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9
<b>Log K<sub>OW</sub></b> : 1.09

### Accumulation / Evaluation:

No further relevant information available.

## 12.4. Mobility in soil

No further relevant information available.

## 12.5. Results of PBT and vPvB assessment

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> EC No.: 921-024-6
<b>Results of PBT and vPvB assessment:</b> —
<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> CAS No.: 106-97-8 EC No.: 203-448-7
<b>Results of PBT and vPvB assessment:</b> —
<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9
<b>Results of PBT and vPvB assessment:</b> —

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 11/14



## Copper Spray 500ml

**copper** CAS No.: 7440-50-8 EC No.: 231-159-6

Results of PBT and vPvB assessment: —

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

### 12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

Toxic to aquatic life. Toxic to fish.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

#### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

#### Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant — skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic








### Waste treatment options

#### Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

Recommended cleaning agent: Water, if necessary with the addition of cleaning agents.

## SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1. UN number or ID number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>			
AEROSOLS, ENVIRONMENTALLY HAZARDOUS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)	AEROSOLS, ENVIRONMENTALLY HAZARDOUS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)	AEROSOLS, MARINE POLLUTANT (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)	AEROSOLS, flammable (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
<b>14.3. Transport hazard class(es)</b>			
 2.1	 2.1	 2.1	 2.1
<b>14.4. Packing group</b>			
-			
<b>14.5. Environmental hazards</b>			
		 MARINE POLLUTANT	No
<b>14.6. Special precautions for user</b>			
<b>Special Provisions:</b> 190   327   344   625	<b>Special Provisions:</b> 190   327   344   625	<b>Special Provisions:</b> 63   190   277   327   344   381   959	<b>Special Provisions:</b> A145   A167

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 12/14



## Copper Spray 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>Limited quantity (LQ):</b> 1 L <b>Excepted Quantities (EQ):</b> E0 <b>Classification code:</b> 5F <b>Tunnel restriction code:</b> (D) <b>Remark:</b> Attention: Gases	<b>Limited quantity (LQ):</b> 1 L <b>Excepted Quantities (EQ):</b> E0 <b>Classification code:</b> 5F <b>Remark:</b> Attention: Gases	<b>Limited quantity (LQ):</b> Siehe SV277 <b>Excepted Quantities (EQ):</b> E0 <b>EmS-No.:</b> F-D, S-U <b>Remark:</b> Attention: Gases	<b>Limited quantity (LQ):</b> Y203 <b>Excepted Quantities (EQ):</b> E0 <b>Remark:</b> Attention: Gases

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU legislation

##### Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

##### Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

##### Other regulations (EU):

Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

- E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 464.1 g/L

#### 15.1.2. National regulations

No data available

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1. Indication of changes

No data available

### 16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

BCF Bioconcentration Factor

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 13/14



## Copper Spray 500ml

CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC <sub>50</sub>	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC <sub>50</sub>	Lethal (fatal) Concentration 50%
LD <sub>50</sub>	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SCL	Specific concentration limit
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
ZNS	central nervous system

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols ( <i>Aerosol 1</i> )	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation ( <i>Skin Irrit. 2</i> )	H315: Causes skin irritation.	
Hazardous to the aquatic environment ( <i>Aquatic Chronic 1</i> )	H410: Very toxic to aquatic life with long lasting effects.	

### 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 2 Aug 2023

**Print date:** 19 Feb 2024

**Version:** 2

Page 14/14



## Copper Spray 500ml

### 16.6. Training advice

No data available

### 16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.