

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 11 Sept 2023

**Print date:** 15 Feb 2024

**Version:** 2



Page 1/13

## Moly Dry 400ml

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Trade name/designation:**

Moly Dry 400ml

**Article No.:**

T270001

**UFI:**

XUH1-ACT5-W00N-CMVT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/mixture:**

Lubricating varnish

#### 1.3. Details of the supplier of the safety data sheet

**Supplier:**

**KANDO Service GmbH**

Hartleitnerstraße 3

4653 Eberstälzell

Austria

**Telephone:** +43 (0) 7241 213 79

**E-mail:** msds@kando.eu

#### 1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols ( <i>Aerosol 1</i> )	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	

#### Additional information:

This mixture does not present an environmental risk. Under normal conditions of use, no environmentally harmful effect is known or foreseeable.

#### 2.2. Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms:**



**GHS02**  
Flame



**GHS07**  
Exclamation mark

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 2/13

## Moly Dry 400ml

**Signal word:** Danger

**Hazard components for labelling:**

butanone; butan-2-ol

### Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

### Hazard statements for health hazards

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

### Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection/face protection.

### Precautionary statements Response

P312	Call a POISON CENTER/doctor if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.

### Precautionary statements Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
-------------	--

## 2.3. Other hazards

**Other adverse effects:**

The mixture does not contain any substance of very high concern (SVHC)  $\geq 0.1\%$  published by the European Chemical Agency (ECHA) according to Article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>. The mixture does not meet the criteria applied to PBT and vPvB mixtures, according to Annex XIII of REACH Directive (EC) No 1907/2006. The mixture does not contain any substance  $\geq 0.1\%$  that is classified as a substance of very high concern (SVHC) according to the criteria of Commission Delegated Regulation (EU) 2017/2100 or the Commission Regulation (EU) 2018/605 has endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients / Hazardous impurities / Stabilisers:**

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 109-87-5 EC No.: 203-714-2 REACH No.: 01-2119664781-31	<b>dimethoxymethane</b> Flam. Liq. 2 (H225) Danger	25 - $\leq$ 50 Vol-%
CAS No.: 78-93-3 EC No.: 201-159-0 REACH No.: 01-2119457290-43	<b>butanone</b> Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger	25 - $\leq$ 50 Vol-%
CAS No.: 78-92-2 EC No.: 201-158-5 Index No.: 603-127-00-5 REACH No.: 01-2119475146-36	<b>butan-2-ol</b> Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Warning	10 - $\leq$ 25 Vol-%

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 3/13

## Moly Dry 400ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 124-38-9 EC No.: 204-696-9	<b>carbon dioxide</b> Press. Gas (Ref. Liq.) (H281) Warning	2.5 - ≤ 10 Vol-%
CAS No.: 14807-96-6 EC No.: 238-877-9 REACH No.: 01-2120140278-58	<b>Diflufenican</b> The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	1 - ≤ 2.5 Vol-%

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information:

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### Following inhalation:

Remove casualty to fresh air and keep warm and at rest.  
Consult a doctor if symptoms persist.  
Do not allow anything to be taken by mouth.

#### In case of skin contact:

Remove contaminated, saturated clothing immediately.  
After contact with skin, wash immediately with plenty of water and soap.  
In case of skin reactions, consult a physician.  
DO NOT use solvents or thinners.

#### After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Consult a doctor if symptoms persist.

#### Following ingestion:

Do not allow anything to be taken by mouth.  
If small amounts are ingested (not more than one sip), rinse mouth with water and consult a doctor.  
Do NOT induce vomiting. Keep at rest.  
Consult a doctor and show him the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Cool endangered containers in the vicinity of the flame with water spray to prevent the containers from bursting under pressure.  
Spray mist, Water with additive AFFF (Aqueous Film Forming Foam), Halon, Foam, ABC-powder, BC-powder, Carbon dioxide

#### Unsuitable extinguishing media:

Water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire, dense black smoke is often produced. Exposure to decomposition products can be harmful to health. Do not inhale smoke.

#### Hazardous combustion products:

Carbon monoxide, carbon dioxide

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 11 Sept 2023

**Print date:** 15 Feb 2024

**Version:** 2



Page 4/13

## Moly Dry 400ml

### 5.3. Advice for firefighters

Due to the toxicity of the gases produced during thermal decomposition, self-contained breathing apparatus (isolation equipment) must be used.

### 5.4. Additional information

Flammable.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### Personal precautions:

Follow protective measures in sections 7 and 8. Remove all sources of ignition. Ventilate affected area. Avoid breathing vapours. Avoid contact with eyes and skin. Wear protective equipment. Keep unprotected persons away.

#### 6.1.2. For emergency responders

##### Personal protection equipment:

Wear personal protection equipment (refer to section 8).

### 6.2. Environmental precautions

Stop and collect leaks or spills with liquid-binding, non-combustible material, e.g.: Sand, earth, universal binder, diatomaceous earth in drums for disposal of waste. Prevent entry into drains or watercourses. If the product pollutes watercourses, rivers or sewage systems, inform the competent authorities in accordance with the prescribed procedure. Set up canisters for disposal of waste generated in accordance with applicable regulations (see section 13).

### 6.3. Methods and material for containment and cleaning up

##### For cleaning up:

Preferably clean with a detergent, do not use organic solvents.

### 6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Protective measures

##### Advices on safe handling:

Precautions for safe handling:

The regulations for storage facilities apply to the premises where the mixture is worked with. Persons with a history of skin sensitisation must not use this mixture under any circumstances.

Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

Ensure good ventilation/extraction at the workplace. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Advices on safe handling:

For personal protection, see section 8. Observe label information and occupational health and safety regulations. Do not inhale aerosol. Avoid inhalation of vapours. Carry out any industrial work with possible formation of vapours/mist etc. in closed apparatus. Provide vapour extraction at the source of emission and general room ventilation. In addition, provide suitable respiratory protective equipment for short-term work and emergency interventions. Always collect emissions at source. Do not allow mixture to come into contact with skin and eyes. Store opened packaging carefully closed and upright.

Improper equipment and method of operation:

Smoking, eating and drinking are prohibited in the premises where the mixture is used. Never open packages with pressure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 5/13

## Moly Dry 400ml

### Fire prevent measures:

Handle in well ventilated areas. Vapours are heavier than air. They can spread on the ground and form explosive mixtures together with air. Prevent the formation of ignitable or explosive vapour-air concentrations. Avoid vapour concentrations above Avoid exposure limits. Do not spray on a flame or glowing object. Do not open by force or burn, even after use. Use the mixture in rooms without open flames or other ignition sources and with protected electrical equipment. Keep container tightly closed when not in use. Keep away from heat sources, sparks or open flames. Do not use tools that can produce sparks. Do not smoke. Prevent access for unauthorised persons.

### Advices on general occupational hygiene

Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels:

Keep only in the original container in a cool, well-ventilated place.

#### Hints on storage assembly:

Keep away from sources of ignition - No smoking.

#### Further information on storage conditions:

Keep only in the original container in a cool, well-ventilated place. Store away from heat, weather, moisture and frost. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

### 7.3. Specific end use(s)

#### Recommendation:

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	① 1,000 ppm (3,100 mg/m <sup>3</sup> )
MAK (AT)	<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	① 100 ppm (295 mg/m <sup>3</sup> ) ⑤ (kann über die Haut aufgenommen werden) H
MAK (AT)	<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	② 200 ppm (590 mg/m <sup>3</sup> ) ⑤ (max. 4x30 min./Schicht, kann über die Haut aufgenommen werden) H
IOELV (EU)	<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m <sup>3</sup> ) ② 300 ppm (900 mg/m <sup>3</sup> )
MAK (AT)	<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	① 50 ppm (150 mg/m <sup>3</sup> )
MAK (AT)	<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	② 200 ppm (600 mg/m <sup>3</sup> ) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	<b>carbon dioxide</b> CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m <sup>3</sup> )
MAK (AT)	<b>carbon dioxide</b> CAS No.: 124-38-9 EC No.: 204-696-9	② 10,000 ppm (18,000 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 6/13

## Moly Dry 400ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	<b>carbon dioxide</b> CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m <sup>3</sup> )
MAK (AT)	<b>Diflufenican</b> CAS No.: 14807-96-6 EC No.: 238-877-9	① 2 mg/m <sup>3</sup> ⑤ (alveolengängige Fraktion)

### 8.1.2. Biological limit values

No data available

### 8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	132 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	39 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	22 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	5.7 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	9.6 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	600 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	106 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	1,161 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	412 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0	31 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	212 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	52 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	405 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	203 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 7/13

## Moly Dry 400ml

Substance name	DNEL value	① DNEL type ② Exposure route
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	15 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	14.577 mg/L	① PNEC aquatic, freshwater
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	1.4577 mg/L	① PNEC aquatic, marine water
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	10 mg/L	① PNEC sewage treatment plant
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	13.135 mg/kg	① PNEC sediment, freshwater
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	1.313 mg/kg	① PNEC sediment, marine water
<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2	4.654 mg/kg	① PNEC soil
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	47.1 mg/L	① PNEC aquatic, freshwater
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	47.1 mg/L	① PNEC aquatic, marine water
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	761 mg/L	① PNEC sewage treatment plant
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	196.19 mg/kg	① PNEC sediment, freshwater
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	196.19 mg/kg	① PNEC sediment, marine water
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	11.58 mg/kg	① PNEC soil
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5	47.1 mg/L	① PNEC aquatic, intermittent release

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

Use clean and properly maintained personal protective equipment. Keep personal protective equipment in a clean place, away from the work area. Do not eat, drink or smoke during use. Remove and wash contaminated clothing before reuse. Provide adequate ventilation, especially in enclosed spaces.

### 8.2.2. Personal protection equipment

#### Eye/face protection:

Avoid contact with eyes. Use eye protection against liquid splashes. Safety goggles complying with standard EN 166 must be worn at all times during use.

In case of increased danger, use a face shield to protect the face. Wearing prescription glasses does not constitute protection. Contact lens wearers are advised to use corrective lenses during work where



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 11 Sept 2023

**Print date:** 15 Feb 2024

**Version:** 2



Page 8/13

## Moly Dry 400ml

irritating fumes may be generated. Provide eye shower systems in the premises where the product is used.

### Skin protection:

Hand protection:

Use suitable chemical-resistant protective gloves according to standard EN ISO 374-1. Gloves must be chosen according to the use and duration of use in the workplace. Protective gloves must be chosen according to the workplace: other chemicals could be changed, physical protection required (cutting, pricking, thermal protection), dexterity required.

Glove material:

PVC (polyvinyl chloride)

NBR (Nitrile rubber)

Skin protection:

In case of heavy splashing, wear liquid-tight chemical protective clothing (type 3) according to EN 14605/A1 to avoid any skin contact. If there is a risk of splashing, wear chemical protective clothing (type 6) according to EN 13034/A1 to avoid any skin contact. Personnel must wear regularly washed work clothes. After contact with the product, all soiled parts of the body must be washed.

### Respiratory protection:

When workers are exposed to concentrations exceeding the exposure limits, they must wear appropriate and approved respiratory protective equipment.

Type of FFP mask:

- FFP1

- FFP2

- FFP3

Gas and steam filter (combi-filter) according to standard EN 14387:

- A1 (brown)

- AX (brown)

Particle filter device (EN 143):

- P1 (white)

- P (white)

### Other protection measures:

Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Ensure good ventilation/extraction at the workplace.

### 8.2.3. Environmental exposure controls

No data available

### 8.3. Additional information

No further relevant information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state:** Aerosol

**Colour:** black

**Odour:** not determined

**Odour threshold:** not determined

#### Safety relevant basis data

Parameter	Value	① Method ② Remark
pH	No data available	
Initial boiling point and boiling range	No data available	
Evaporation rate	No data available	
Upper/lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative density	0.87	
Bulk density	not applicable	



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2

Page 9/13



## Moly Dry 400ml

Parameter	Value	① Method ② Remark
Water solubility	partially soluble	

### 9.2. Other information

No further relevant information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No further relevant information available.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

At high temperatures, the mixture may release hazardous decomposition products, such as carbon monoxide, carbon dioxide, smoke or nitrogen oxide.

### 10.4. Conditions to avoid

The operation of devices/work equipment that produce flames or sparks or heat a metal surface (e.g. burners, electric arches, ovens, etc.) is not permitted in the work area/rooms. Avoid: Heating, heat, electrical charge, flames and hot surfaces, frost, ignition sources.

### 10.5. Incompatible materials

Acids, Oxidizing agent

### 10.6. Hazardous decomposition products

Carbon monoxide, Carbon dioxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0
<b>LD<sub>50</sub> oral:</b> >2,193 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> 40 mg/L (Mouse)
<b>carbon dioxide</b> CAS No.: 124-38-9 EC No.: 204-696-9
<b>ATE (inhalation, vapour):</b> 259,354 mg/L
<b>LD<sub>50</sub> oral:</b> ≥5,000 mg/kg (Ratte)
<b>LD<sub>50</sub> dermal:</b> ≥5,000 mg/kg (Kaninchen)
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> ≥50 mg/L 4 h (Ratte)

#### Acute oral toxicity:

Based on available data, the classification criteria are not met.

#### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

#### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation:

Splashes in the eyes may cause irritation and reversible damage. May cause reversible effects to the eye, such as eye irritation, which completely resolves in an observation period of 21 days.

#### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2

Page 10/13



## Moly Dry 400ml

### Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

### STOT-single exposure:

Based on available data, the classification criteria are not met.

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Prolonged or repeated contact with the mixture may eliminate the natural greasy film of the skin and therefore cause non-allergic contact dermatitis and penetration of the epidermis. Narcotic effects may occur, such as drowsiness, narcotic effect, decreased attention, loss of reflexes, incoordination and dizziness. They may also manifest as severe headache or nausea and lead to decreased judgement, drowsiness, irritability, fatigue or memory impairment.

### Additional information:

Exposure to vapours of the solvent contained in this mixture in excess of the specified exposure limits may cause adverse health effects such as mucous membrane and respiratory tract irritation, kidney, liver and central nervous system disorders. Symptoms/signs include headache, dizziness, nausea, fatigue, muscle pain and in extreme cases unconsciousness.

## 11.2. Information on other hazards

### Endocrine disrupting properties:

None of the ingredients are included.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0
<b>LC<sub>50</sub></b> : 2,993 mg/L 4 d (fish, <i>Pimephales promelas</i> ) OECD 203
<b>EC<sub>50</sub></b> : 308 mg/L 2 d (crustaceans, <i>Daphnia magna</i> ) OECD 202
<b>ErC<sub>50</sub></b> : 1,972 mg/L 3 d (Algae/water plant, <i>Pseudokirchnerella subcapitata</i> ) OECD 201
<b>Diflufenican</b> CAS No.: 14807-96-6 EC No.: 238-877-9
<b>LC<sub>50</sub></b> : >100 mg/L 1 d

### Aquatic toxicity:

No further relevant information available.

### Additional ecotoxicological information:

No further relevant information available.

### 12.2. Persistence and degradability

<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0
<b>Biodegradation</b> : Yes, rapidly

### Abiotic degradation:

No further relevant information available.

### Biodegradation:

No further relevant information available.

### 12.3. Bioaccumulative potential

#### Accumulation / Evaluation:

No further relevant information available.

### 12.4. Mobility in soil

No further relevant information available.

### 12.5. Results of PBT and vPvB assessment

<b>dimethoxymethane</b> CAS No.: 109-87-5 EC No.: 203-714-2
<b>Results of PBT and vPvB assessment</b> : —

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 11/13

## Moly Dry 400ml

<b>butanone</b> CAS No.: 78-93-3 EC No.: 201-159-0
<b>Results of PBT and vPvB assessment:</b> —
<b>butan-2-ol</b> CAS No.: 78-92-2 EC No.: 201-158-5
<b>Results of PBT and vPvB assessment:</b> —
<b>carbon dioxide</b> CAS No.: 124-38-9 EC No.: 204-696-9
<b>Results of PBT and vPvB assessment:</b> —
<b>Diflufenican</b> CAS No.: 14807-96-6 EC No.: 238-877-9
<b>Results of PBT and vPvB assessment:</b> —

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

None of the ingredients are included.

### 12.7. Other adverse effects

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

#### Waste treatment options





##### Appropriate disposal / Product:

Waste disposal must be carried out without risk to people and the environment, in particular to water, air, soil, fauna and flora. Disposal or recycling in accordance with valid legislation preferably by an authorised waste collector or a specialist waste management company. Do not contaminate soil or groundwater, do not dispose of waste in the environment.

##### Appropriate disposal / Package:

Uncleaned packaging: Only dispose of the container when it is empty. Do not remove the label(s) on the container. Return to an authorised disposal company.

## SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1. UN number or ID number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>			
AEROSOLS, FLAMMABLE	AEROSOLS, FLAMMABLE	AEROSOLS, flammable	AEROSOLS, flammable
<b>14.3. Transport hazard class(es)</b>			
 2.1	 2.1	 2.1	 2.1
<b>14.4. Packing group</b>			
		-	
<b>14.5. Environmental hazards</b>			
No	No	No	No
<b>14.6. Special precautions for user</b>			
<b>Special Provisions:</b> 190   327   344   625 <b>Limited quantity (LQ):</b> 1 L <b>Excepted Quantities (EQ):</b> E0 <b>Classification code:</b> 5F	<b>Special Provisions:</b> 190   327   344   625 <b>Limited quantity (LQ):</b> 1 L <b>Excepted Quantities (EQ):</b> E0 <b>Classification code:</b> 5F	<b>Special Provisions:</b> 63   190   277   327   344   381   959 <b>Limited quantity (LQ):</b> Siehe SV277 <b>Excepted Quantities (EQ):</b> E0	<b>Special Provisions:</b> A145   A167   A802 <b>Limited quantity (LQ):</b> Y203 <b>Excepted Quantities (EQ):</b> E0

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 11 Sept 2023

Print date: 15 Feb 2024

Version: 2



Page 12/13

## Moly Dry 400ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>Tunnel restriction code:</b> (D)	<b>Remark:</b> IATA Packing Instructions - Passenger: 203 IATA Maximum Quantity - Passenger: 75kg IATA- Verpackungsanweisung - Cargo: 203 IATA Maximum Quantity - Cargo: 150kg	<b>EmS-No.:</b> F-D, S-U <b>Remark:</b> Stowage Handling: - SW1 SW22	<b>Remark:</b> IATA Packing Instructions - Passenger: forbidden IATA Maximum Quantity - Passenger: forbidden IATA- Verpackungsanweisung - Cargo: 203 IATA Maximum Quantity - Cargo: 150 KG

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1. Indication of changes

No data available

### 16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC <sub>50</sub>	Effective Concentration 50%
ECHA	European Chemicals Agency
EN	European Standard
ES	Exposure scenario
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC <sub>50</sub>	Lethal (fatal) Concentration 50%
LD <sub>50</sub>	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SVHC	substances of very high concern

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 11 Sept 2023

**Print date:** 15 Feb 2024

**Version:** 2



Page 13/13

## Moly Dry 400ml

TRGS Technische Regeln für Gefahrstoffe  
UN United Nations  
ZNS central nervous system

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols ( <i>Aerosol 1</i> )	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	

### 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H281	Contains refrigerated gas; may cause cryogenic burns or injury.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

### 16.6. Training advice

No data available

### 16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.