according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 6 Jul 2023 Print date: 15 Feb 2024 TECH MASTERS

Version: 2 Page 1/13

PUR Foam Cleaner 500ml

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

PUR Foam Cleaner 500ml

Article No.: T670701 UFI:

GKE6-DJGD-DD0U-8CPE

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 2/13

PUR Foam Cleaner 500ml

Hazard components for labelling:

acetone

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229 Pressurised container: May burst if heated.		
Hazard statements for health hazards		
11210		

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing and eye protection/face protection.	

Precautionary statements Response

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

Other adverse effects:

The product does not meet the PBT/vPvB criteria.

The product does not meet the criteria regarding its endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Solvent

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336)	60 - < 100 Vol-%
CAS No.: 115-10-6 EC No.: 204-065-8 Index No.: 603-019-00-8 REACH No.: 01-2119472128-37	dimethyl ether Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	20 - < 40 Vol-%

Full text of H- and EUH-phrases: see section 16.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2

Page 3/13

PUR Foam Cleaner 500ml

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Symptoms of poisoning may occur after contact, so if in doubt, consult a doctor in case of direct contact with the chemical product or persistence of indisposition, and present the safety data sheet of this product to the doctor.

Following inhalation:

Remove the victim from the exposure site, provide him/her with clean air and keep him/her in a resting position. In severe cases such as cardio-respiratory arrest, apply artificial respiration techniques (mouth-to-mouth resuscitation, cardiac massage, oxygen supply, etc.). Medical advice should be sought immediately.

In case of skin contact:

Remove contaminated clothing and shoes, rinse the skin or, if necessary, shower the affected person with plenty of cold water and neutral soap. In severe cases, consult a doctor. If the mixture causes burns or frostbite, do not remove the clothing, as the injury caused may be aggravated if it sticks to the skin. If blisters form on the skin, do not puncture them as this increases the risk of infection.

After eye contact:

Flush eyes with plenty of water for at least 15 minutes. If the affected person wears contact lenses, remove them as far as they do not stick to the eyes, otherwise additional injuries may occur. In all cases, a doctor must be consulted as soon as possible after washing and the safety data sheet presented to him.

Following ingestion:

Do NOT induce vomiting. If vomiting occurs, hold the head forward to avoid inhalation. Keep the person in a resting position. Rinse mouth and throat as they may have been affected by ingestion.

4.2. Most important symptoms and effects, both acute and delayed The immediate and delayed effects are given in sections 2 and 11.

4.3. Indication of any immediate medical attention and special treatment needed not relevant

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

ABC-powder, Foam, Carbon dioxide (CO2)

Unsuitable extinguishing media:

Water jet

5.2. Special hazards arising from the substance or mixture

As a result of combustion or thermal decomposition, reactive sub-products are formed that can be highly toxic and therefore pose a high and can therefore pose a high health risk.

5.3. Advice for firefighters

Depending on the size of the fire, it may be necessary to use full protective clothing and autonomous breathing apparatus may be required. There should be a minimum stock of emergency facilities or equipment (fireproof blankets, portable first aid kit, ...) in accordance with Directive 89/654/EC. first-aid kit, ...) should be available in accordance with Directive 89/654/EC.

5.4. Additional information

Proceed in accordance with the internal emergency plan and the information sheets on what to do in the event of accidents and other emergencies. proceed. Keep away all sources of ignition. In case of fire, cool the storage containers and tanks of products that may catch fire or explode or explode or are at risk of BLEVE due to elevated temperatures. The leakage of products used in Avoid leakage of products used in firefighting into groundwater.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2

Page 4/13

PUR Foam Cleaner 500ml

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Isolate leaks as far as this does not pose an additional risk to the persons involved. Evacuate area and keep away persons without protective equipment. In view of possible contact with the spilled product, the use of personal protective equipment is mandatory (see section 8). Above all, prevent the formation of flammable vapour-air mixtures, either by ventilation or by using a neutralising agent. Keep away all sources of ignition. Prevent electrostatic charges by connecting all conductor surfaces on which static electricity can build up, again keeping them earthed as a whole.

6.1.2. For emergency responders

Personal protection equipment:

See section 8.

6.2. Environmental precautions

The product is not classified as dangerous for the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information:

Soak up spilled product using sand or neutral absorbent material and take to a safe place. Do not absorb with Do not absorb with sawdust or other flammable absorbents. Disposal: See section 13.

6.4. Reference to other sections

See section 7 for further information on safe handling. For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Comply with the legislation in force on the prevention of industrial risks. Keep containers hermetically closed. Keep spilled substances and residues under control and dispose of by safe methods (section 6). Avoid leakage from the container. Places where hazardous products are handled must be kept tidy and clean.

Fire prevent measures:

Product is not flammable under normal conditions of storage, handling and use. Slow decanting is recommended to avoid the build-up of electrostatic charges that could affect flammable products.

Environmental precautions:

Due to the hazardous nature of this product to the environment, it is recommended that it be handled within an area that has contamination control barriers in the event of a spill and that absorbent material be stored nearby.

Advices on general occupational hygiene

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Store in a cool dry place.

Requirements for storage rooms and vessels:

Avoid sources of heat, radiation, static electricity and contact with food. Further information (see section 10.5).

7.3. Specific end use(s)

Recommendation:

No further relevant information available.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 6 Jul 2023

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2

Page 5/13

PUR Foam Cleaner 500ml

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	 2,000 ppm (4,800 mg/m³) (max. 4x15 min./Schicht)
IOELV (EU)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	 500 ppm (1,210 mg/m³)
MAK (AT)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,200 mg/m³)
MAK (AT)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	 1,000 ppm (1,910 mg/m³)
MAK (AT)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	 2,000 ppm (3,820 mg/m³) (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	 1,000 ppm (1,920 mg/m³)

8.1.2. Biological limit values No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m ³	 DNEL worker Acute - inhalation, local effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	1,894 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 6/13

PUR Foam Cleaner 500ml

Substance name	DNEL value	 DNEL type Exposure route
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	471 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	 PNEC sewage treatment plant
acetone CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	29.5 mg/kg	① PNEC soil
acetone CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.155 mg/L	① PNEC aquatic, freshwater
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.016 mg/L	① PNEC aquatic, marine water
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.681 mg/kg	① PNEC sediment, freshwater
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.069 mg/kg	① PNEC sediment, marine water
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	0.045 mg/kg	① PNEC soil
dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	1.549 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment



Eye/face protection:

Panorama safety goggles against splashes and / or ejection CE marking: CE CAT II EN 166:2002; EN ISO 4007:2018

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2 TECH MASTERS

Page 7/13

PUR Foam Cleaner 500ml

Clean daily and disinfect at regular intervals according to the manufacturer's instructions. Use when there is a risk of splashing is recommended.

Skin protection:

Hand protection: Disposable gloves, Reusable gloves Glove material: Linear low density polyethylene (LLPDE) Permeation time (maximum wear duration): < 480 min. Thickness of the glove material: 0,062mm CE marking: CE CAT III EN 420:2004+A1:2010 Replace gloves at any sign of damage. As the product is a mixture of different materials, the resistance of the glove material cannot be calculated in advance and must be verified shortly before use.

Body protection: Wear suitable work clothing. CE marking: CE CAT I Replace before signs of deterioration appear. CE III is recommended for professional/industrial users exposed to the substance for prolonged periods, in accordance with EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994 regulations.

Non-slip work footwear CE marking: CE CAT II EN ISO 20347:2012 Replace before signs of deterioration appear. CE III is recommended for professional/industrial users exposed to the fabric for prolonged periods, in accordance with EN ISO 20345:2012 and EN 13832-1:2007 regulations.

Respiratory protection:

The use of protective equipment is required in case of fog formation or in case of exceeding the limits for professional exposure limits are exceeded.

Other protection measures:

According to the order of priority for workplace control, local extraction in the work zone is recommended as a collective protective measure to avoid exceeding the limit values in the workplace. In case of using personal protective equipment, it must have the "CE marking"". For more information on personal protective equipment (storage, use, cleaning, maintenance, protection class,...), see the leaflet provided by the manufacturer. The instructions provided in this article refer to the pure product. Protective measures for the diluted product may vary depending on the degree of dilution, application and application procedure, etc. To determine the required installation of emergency showers or eyewashes in the storage rooms, the regulations for the storage of chemicals applicable in each case are taken into account. For more information, see sections 7.1 and 7.2.

Non-slip work footwear:

Emergency shower: ANSI Z358-1; ISO 3864-1:2011, ISO 3864-4:2011 Eye wash: DIN 12 899; ISO 3864-1:2011, ISO 3864-4:2011

8.2.3. Environmental exposure controls

Taking into account Community legislation on environmental protection, it is recommended to avoid leakage of both the product and its packaging into the environment. For further information, see section 7.1.

VOC value: 100% Density: 736 kg/m³ (736 g/L)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol **Odour:** not determined

Colour: colourless

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 8/13

PUR Foam Cleaner 500ml

Safety relevant basis data

Parameter	Value	at °C	1 Method
			② Remark
рН	7 - 7.4		
Initial boiling point and boiling range	-25 °C		② Propellant gas
Evaporation rate	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	< 300 kPa	50 °C	
Density	736 kg/m ³	20 °C	
Bulk density	not applicable		
Water solubility	No data available		
Self ignition temperature	240 °C		② Propellant gas

9.2. Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Chemically stable under conditions of storage, handling and use.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Avoid high temperatures or direct sunlight.

10.5. Incompatible materials

Avoid strong acids, alkalis and bases. Avoid direct exposure to materials that promote combustion.

10.6. Hazardous decomposition products

See sections 10.3, 10.4 and 10.5 for specific degradation products. Depending on the degradation conditions, complex mixtures of chemical substances may be released during degradation: Carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information

Acute Toxicity Estimate for Mixtures ATE (oral): >2,000 mg/kg ATE (dermal): >2,000 mg/kg ATE (inhalation, dust/mist): >20 mg/L acetone CAS No.: 67-64-1 EC No.: 200-662-2 ATE (oral): 5,800 mg/kg ATE (dermal): 20,000 mg/kg ATE (inhalation, dust/mist): 76 mg/L LD₅₀ oral: 5,800 mg/kg (Rat) LD₅₀ dermal: >7,800 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 9/13

PUR Foam Cleaner 500ml

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8	
--	--

LD₅₀ oral: >2,000 mg/kg

LD₅₀ dermal: >2,000 mg/kg

LC₅₀ Acute inhalation toxicity (dust/mist): 308.5 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes eye injuries after contact.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Exposure at high concentrations may cause central nervous system depression and headache, dizziness, nausea, vomiting, confusion and in severe cases loss of consciousness.

STOT-repeated exposure:

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

The product does not meet the criteria regarding its endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

acetone CAS No.: 67-64-1 EC No.: 200-662-2

LC₅₀: 8,300 mg/L 4 d (fish)

LC₅₀: 8,450 mg/L 2 d (crustaceans)

EC₅₀: 7,200 mg/L 4 d (Algae/water plant)

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8

LC₅₀: >4,000 mg/L 2 d (crustaceans, Daphnia magna)

LC₅₀: >4,000 mg/L 4 d (fish)

EC₅₀: 155 mg/L 4 d (Algae/water plant)

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Biodegradation: Yes, rapidly

Additional information:

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2

Page 10/13

PUR Foam Cleaner 500ml

12.3. Bioaccumulative potential

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Log K_{OW}: -0.24

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Results of PBT and vPvB assessment: -

dimethyl ether CAS No.: 115-10-6 EC No.: 204-065-8

Results of PBT and vPvB assessment: -

The product contains PBT / vPvB: Chloralkane, C14-C17

12.6. Endocrine disrupting properties

The product does not meet the criteria regarding its endocrine disrupting properties.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of by the authorised waste manager in accordance with the recovery and disposal operations set out in Annex 1 and Annex 2 (Directive 2008/98/EC). According to codes 15 01 (2014/955/EC), if the container has been in direct contact with the product, treat it in the same way as the product itself, otherwise as if there were no hazardous residues. Do not allow to enter drains. See section 6.2.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

16 05 04 * Gases in pressure containers (including halons) containing hazardous substances

*: Evidence for disposal must be provided. Directive 2008/98/EC (Waste Framework Directive)

υ	Directive 2008/98/EC (Waste Framework Directive)					
	HP 3	Flammable				
	HP 4	Irritant — skin irritation and eye damage				
	HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity				

Waste treatment options

Appropriate disposal / Product:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH), the Community or national provisions regarding waste recovery shall be complied with. Community legislation: Directive 2008/98/ EC, 2014/955/EC, Regulation (EU) No 1357/2014. National regulations: Act on the Reorganisation of the Recycling and Waste Management Law. Of 24 February 2012.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)			
14.1. UN number or ID number						
UN 1950	UN 1950	UN 1950	UN 1950			
14.2. UN proper shipping name						
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS			



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 11/13

PUR Foam Cleaner 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.3. Transport haza	rd class(es)		,
2.1	2.1		
14.4. Packing group		2.1	2.1
		-	
14.5. Environmental	hazards		
No	No	No	No
14.6. Special precau	tions for user	*	
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D)	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U	Special Provisions: A145 A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Substances for which authorisation in Regulation (CE) 1907/2006 (REACH) is pending: Not relevant. Substances included in REACH Annex XIV (authorisation list) and expiry date: Not relevant. Regulation (EC) 1005/2009 on ozone depleting substances Not relevant. Article 95, REGULATION (EU) No 528/2012: Not relevant. REGULATION (EU) No 649/2012 on the export and import of dangerous chemical substances: Not relevant.

Other regulations (EU):

Hazard categories:

• P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas **Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:** Volatile organic compounds (VOC) content in percent by weight: 100 Vol-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2



Page 12/13

PUR Foam Cleaner 500ml

16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists ACGIH ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways European Agreement concerning the International Carriage of Dangerous Goods by Road ADR **Bioconcentration Factor** BCF CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging derived no-effect level DNEL Effective Concentration 50% EC₅₀ ES Exposure scenario European Waste Catalogue EWC IARC International Agency for Research on Cancer **ICAO** International Civil Aviation Organization International Maritime Dangerous Goods IMDG International Maritime Organization IMO body weight KG LC_{50} Lethal (fatal) Concentration 50% Lethal (fatal) Dose 50% LD_{50} MAK Maximum concentration in the workplace air (CH) NFPA National Fire Protection Association NIOSH National Institute for Occupational Safety & Health No Observed Effect Concentration NOEC Organisation for Economic Cooperation and Development OECD Occupational Safety & Health Administration OSHA PBT persistent and bioaccumulative and toxic PNEC Predicted No Effect Concentration Registration, Evaluation and Authorization of Chemicals REACH Dangerous goods regulations for transport by rail RID Specific concentration limit SCL Technische Regeln für Gefahrstoffe TRGS UN United Nations VOC Volatile organic compounds central nervous system ZNS

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements

Hazard statements		
H220	Extremely flammable gas.	
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	1
H319	Causes serious eye irritation.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Jul 2023 Print date: 15 Feb 2024 Version: 2 TECH MASTERS world of innovations

Page 13/13

EUH066

PUR Foam Cleaner 500ml

Hazard statements

H336 May cause drowsiness or dizziness.

Supplemental hazard information

Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.