according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 1/13

PU Fix white 50ml (Comp. B)

TECH MASTERS world of innovations

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

PU Fix white 50ml (Comp. B)

Article No.:

T915050 UFI: VPK0-EPRW-N901-XYNX

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Adhesive

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	
Respiratory or skin sensitisation (Resp. Sens. 1)	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 2/13

PU Fix white 50ml (Comp. B)



2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



Signal word: Danger

Hazard components for labelling:

Diphenylmethandiisocyanat, Isomere und Homologe; 4,4'-methylenediphenyl diisocyanate

Hazard statements for health hazards		
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
Supplemental hazard information		

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements Prevention	
P201	Obtain special instructions before use.
P260	Do not breathe vapours and spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P284	Wear respiratory protection.

Precautionary statements Response

riceautionary stat	recould only statements response	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P308 + P313	IF exposed or concerned: Get medical advice/attention.	

Additional information:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product does not contain any substances with endocrine-disrupting properties in concentrations of ≥ 0.1%.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 3/13

PU Fix white 50ml (Comp. B)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 9016-87-9 REACH No.: 01-2119456816-28	Diphenylmethandiisocyanat, Isomere und Homologe Acute Tox. 4 (H332), Carc. 2 (H351), Eye Irrit. 2 (H319),	
CAS No.: 101-68-8 EC No.: 202-966-0 Index No.: 615-005-00-9 REACH No.: 01-2119457014-47	4,4'-methylenediphenyl diisocyanate Acute Tox. 4 (H332), Carc. 2 (H351), Eye Irrit. 2 (H319), Resp. Sens. 1 (H334), STOT RE 2 (H373**), STOT SE 3 (H335), Skin Irrit. 2 (H315), Skin Sens. 1 (H317)	1 - 5 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Never give anything by mouth to an unconscious person!

Following inhalation:

Remove person from danger zone.

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

Wash with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. In case of skin irritation, consult a physician.

After eye contact:

First rinse with water for a long time, (remove contact lenses if this is easily possible), then consult a doctor.

Following ingestion:

Rinse mouth thoroughly with water. Drink plenty of water. Call a physician immediately.

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

If applicable, delayed symptoms and effects can be found in section 11. or in the routes of intake under section 4.1.

Symptoms of poisoning may not appear for many hours, therefore medical monitoring for at least 48 hours after an accident.

It may occur: Irritation of the eyes, irritation of the skin, irritation of the mucous membranes of the nose and throat, irritation of the respiratory tract, chest pain, cough. In case of sensitisation, even concentrations below the limit value may result in signs of asthma.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 4/13

PU Fix white 50ml (Comp. B)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Adapt fire extinguishing measures to the surroundings.

Water spray jet, Foam, Carbon dioxide (CO2), Dry extinguishing powder

Unsuitable extinguishing media:

None known

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

Carbon oxides, Nitrogen oxides, Hydrogen cyanide (hydrocyanic acid), toxic gases

5.3. Advice for firefighters

Personal protection equipment: see section 8. Do not inhale explosion and combustion gases. Use suitable breathing apparatus. Depending on the size of the fire, full protection if necessary. Cool endangered containers with water spray. Fire residues and contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove all sources of ignition. Avoid dust formation with solid or powdery products. Wear protective equipment. Keep unprotected persons away. Avoid contact with skin, eyes and clothes. If necessary, observe the risk of slipping.

Emergency procedures:

Leave the danger zone as far as possible, use existing emergency plans if necessary.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Contain in case of escape of larger quantities. Stop leak if safe to do so. Do not allow to enter into surface water or drains. Prevent the product from entering waste water, surface water, ground water. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:

Pour the collected material into a sealable container.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace. Avoid breathing vapours. Avoid contact with skin, eyes and clothes. Do not use these products if you suffer from allergies, asthma or chronic respiratory diseases. When using do not eat, drink, smoke, sniff. Take care for the labels and safety data sheets of the chemicals to be used.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



Page 5/13

PU Fix white 50ml (Comp. B)

Advices on general occupational hygiene

The usual precautions when handling chemicals must be observed. Wash hands before breaks and after work. Keep away from food, drink and animal feed. Remove contaminated clothing and protective equipment before entering areas where food will be served.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Prevent access for unauthorised persons.

Requirements for storage rooms and vessels:

Do not store product in passageways and stairways. Keep only in the original container in a cool, wellventilated place. Store in a cool dry place.

Storage class (TRGS 510, Germany): 10 – Combustible liquids that cannot be assigned to any of the above storage classes

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	① 0.005 ppm (0.05 mg/m³) ⑤ III B, Sah
MAK (AT)	4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	 ② 0.01 ppm (0.1 mg/m³) ⑤ (max. 8x5 min./Schicht, Momentanwert) III B, Sah

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.025 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.05 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.1 mg/m ³	 DNEL worker Acute - inhalation, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.05 mg/m ³	 DNEL Consumer Acute - inhalation, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.05 mg/m ³	 DNEL worker Long-term - inhalation, local effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.025 mg/m ³	 DNEL Consumer Long-term - inhalation, local effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



Page 6/13

PU Fix white 50ml (Comp. B)

Substance name	DNEL value	DNEL type The second
		② Exposure route
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.1 mg/m³	 DNEL worker Acute - inhalation, local effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	0.05 mg/m ³	 DNEL Consumer Acute - inhalation, local effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	50 mg/kg bw/ day	 DNEL worker Acute - dermal, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	25 mg/kg bw/ day	 DNEL Consumer Acute - dermal, systemic effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	28.7 mg/cm ²	 DNEL worker Acute - dermal, local effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	17.2 mg/cm ²	 DNEL Consumer Acute - dermal, local effects
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	20 mg/kg bw/ day	 DNEL Consumer Acute - oral, systemic effects
	1	· · · · · · · · · · · · · · · · · · ·
Substance name	PNEC Value	① PNEC type
Substance name 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0	PNEC Value 3.7 μg/L	 PNEC type PNEC aquatic, freshwater
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8		
 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 	3.7 μg/L	① PNEC aquatic, freshwater
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8	3.7 μg/L 0.37 μg/L	 PNEC aquatic, freshwater PNEC aquatic, marine water
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8	3.7 μg/L 0.37 μg/L 1 mg/L 11.7 mg/kg	 PNEC aquatic, freshwater PNEC aquatic, marine water PNEC sewage treatment plant
 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0 4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 	 3.7 μg/L 0.37 μg/L 1 mg/L 11.7 mg/kg bw/day 1.17 mg/kg 	 PNEC aquatic, freshwater PNEC aquatic, marine water PNEC sewage treatment plant PNEC sediment, freshwater

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation. This can be achieved by local exhaust ventilation or general exhaust air. If this is not sufficient to keep the concentration below the occupational exposure limits (OEL), suitable respiratory protection must be worn. Applies only if exposure limits are listed here. Appropriate assessment methods for verifying the effectiveness of the protective measures taken include metrological and non-measured methods of determination. Such methods are described by e.g. EN 14042, TRGS 402 (Germany). EN 14042 "Workplace atmospheres. Guidance for the application and use of methods and equipment for the determination of chemical and biological agents". TRGS 402 (Germany) "Determining and assessing the hazards of activities involving hazardous substances - Inhalation exposure".

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 7/13

PU Fix white 50ml (Comp. B)

8.2.2. Personal protection equipment

Eye/face protection:

Safety goggles with side shields (EN 166).

Skin protection:

Hand protection: Chemical resistant protective gloves (EN ISO 374). Glove material: Butyl caoutchouc (butyl rubber) Neoprene® NBR (Nitrile rubber)

PVC (polyvinyl chloride)

Thickness of the glove material: 0,5mm

Breakthrough time: >= 480 min.

The determined breakthrough times according to EN 16523-1 were not carried out under practical conditions. A maximum wearing time corresponding to 50% of the breakthrough time is recommended. Hand protection cream recommended.

Additional information on hand protection - No tests have been carried out. For mixtures, the selection was made to the best of our knowledge and based on the information provided by the ingredients. For substances, the selection was derived from the glove manufacturer's information. Final selection of glove material must be made with consideration of breakthrough times, permeation rates and degradation. The selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer. In the case of mixtures, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. The exact breakthrough time of the glove material must be obtained from the protective glove manufacturer and must be observed.

Body protection:

Protective work clothing (e.g. safety shoes EN ISO 20345, long-sleeved work clothing).

Respiratory protection:

If the occupational exposure limit value (AGW, Germany) or MAK (Switzerland, Austria) is exceeded. Respirator filter ABEK-P2 (EN 14387), identification colour brown, grey, yellow, green, white. Observe the wear time limits as specified by the manufacturer.

Thermal hazards:

Not required.

Other protection measures:

The usual precautions when handling chemicals must be observed.

Wash hands before breaks and after work.

Keep away from food, drink and animal feed.

Remove contaminated clothing and protective equipment before entering areas where food will be served.

8.2.3. Environmental exposure controls

No further relevant information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

No data available

No data available

No data available

Appearance

Freezing point

Flash point

Initial boiling point and boiling range

	Physical state: Paste Odour: mild	Colour: brown	
S	Safety relevant basis data		
	Parameter	Value	1 Method
			② Remark
	рН	No data available	
	Melting point	No data available	



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



Page 8/13

PU Fix white 50ml (Comp. B)

Parameter	Value	 Method 	
		② Remark	
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	1.2 g/cm ³		
Relative density			
Bulk density	not applicable		
Water solubility	practically insoluble		
Dynamic viscosity	22 Pa* s		
Kinematic viscosity	No data available		

9.2. Other information

The product is not explosive.

9.2.1. Information with regard to physical hazard classes

Oxidizing liquids:

No.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product has not been tested.

10.2. Chemical stability

Chemically stable under conditions of storage, handling and use.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Avoid heating.

10.5. Incompatible materials

Alkalis, strong oxidants, Acids

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information

Acute Toxicity Estimate for Mixtures		
ATE (inhalation, gases): 2.1 ppmV calculated.		
ATE (inhalation, vapour): 15.421 mg/L calculated.		
Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9		
ATE (inhalation, vapour): 1.5 mg/L		
LD ₅₀ oral: >5,000 mg/kg (Rat) OECD 401		
LD ₅₀ dermal: >5,000 mg/kg (Rabbit) OECD 402		
LC ₅₀ Acute inhalation toxicity (vapour): 0.31 - 0.49 mg/L (Rat) OECD 403		
4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0		
LD ₅₀ oral: >2,000 mg/kg (Rat)		
LD ₅₀ dermal: >9,400 mg/kg (Rabbit) OECD 402		
LC ₅₀ Acute inhalation toxicity (vapour): 0.368 mg/L (Rat) OECD 403		

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



Page 9/13

PU Fix white 50ml (Comp. B)

Acute oral toxicity:
Based on available data, the classification criteria are not met.
Acute dermal toxicity:
Based on available data, the classification criteria are not met.
Skin corrosion/irritation:
Based on available data, the classification criteria are not met.
Serious eye damage/irritation:
Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation:
Based on available data, the classification criteria are not met.
Germ cell mutagenicity:
Based on available data, the classification criteria are not met.
Carcinogenicity:
Based on available data, the classification criteria are not met.
Reproductive toxicity:
Based on available data, the classification criteria are not met.
STOT-single exposure:
Based on available data, the classification criteria are not met.
STOT-repeated exposure:
Based on available data, the classification criteria are not met.
Aspiration hazard:
Based on available data, the classification criteria are not met.
Additional information: No further relevant information available.
11.2. Information on other hazards
Endocrine disrupting properties:
None of the ingredients are included

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

Diph	nenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9				
NC	DEC: >1,000 mg/L (Avena sativa) OECD 208				
NOEC: ≥10 mg/L 21 d (crustaceans, Daphnia magna) OECD 211EC50: >1,000 mg/L (crustaceans, Daphnia magna) OECD 202					
4,4'-	-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0				
LC	C₅₀: >1,000 mg/L 4 d (fish, Brachydanio rerio) OECD 203				
EC	C ₅₀ : >1,000 mg/L (crustaceans, Daphnia magna) OECD 202				
ErC₅₀: >1,640 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) OECD 201					
NC	DEC: >10 mg/L				
lo fu	ssment/classification: urther relevant information available.				
	. Persistence and degradability nenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9				
	odegradation: Poorly biodegradable.				
	emark: Not biodegradable, polyurea is inert and not degradable according to experience to date, slowly reacts th water at the interface with the formation of CO2 to form a solid, highly melting and insoluble reaction produc				

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



Page 10/13

PU Fix white 50ml (Comp. B)

4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0

Biodegradation: Poorly biodegradable.

Remark: Not biodegradable, polyurea is inert and not degradable according to experience to date, slowly reacts with water at the interface with the formation of CO2 to form a solid, highly melting and insoluble reaction product (polyurea).

Additional information:

Slowly reacts with water at the interface to form CO2 and a solid, highly fusible and insoluble reaction product (polyurea). According to experience to date, polyurea is inert and non-degradable.

12.3. Bioaccumulative potential

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9

Bioconcentration factor (BCF): < 14

4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0

Log K_{OW}: 5.22

Bioconcentration factor (BCF): 200

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9

Results of PBT and vPvB assessment:

4,4'-methylenediphenyl diisocyanate CAS No.: 101-68-8 EC No.: 202-966-0

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

None of the ingredients are included.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 04 09 * Waste adhesives and sealants containing organic solvents or other dangerous substances *: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Disposal via waste water is not recommended. Observe local regulations. For example, suitable incineration plant. Cured product: Can be disposed of with household waste.

Appropriate disposal / Package:

Uncleaned packaging: Observe local regulations. Empty container completely. Non-contaminated packaging can be reused. Packaging that cannot be cleaned must be disposed of in the same way as the substance.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3



PU Fix white 50ml (Comp. B)

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number	·	,
No dangerous good in sense of these transport regulations.			
14.2. UN proper ship	ping name		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport haza	rd class(es)	•	,
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental	hazards		
not relevant	not relevant	not relevant	not relevant
14.6. Special precau	tions for user		
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Regulation (EC) No 1907/2006 ANNEX XVII: 4,4'-methylenediphenyl diisocyanate, Diphenylmethandiisocyanat, Isomere und Homologe

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

- ACGIH American Conference of Governmental Industrial Hygienists
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- AGW Threshold Limit Value
- BCF Bioconcentration Factor
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging
- DIN German Institute for Standardization / German Industrial Standard
- DNEL derived no-effect level
- EC₅₀ Effective Concentration 50%
- EN European Standard

ES Exposure scenario

EWC European Waste Catalogue



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3 TECH MASTERS

Page 12/13

PU Fix white 50ml (Comp. B)

IC ₅₀	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SCL	Specific concentration limit
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations

16.3. Key literature references and sources for data No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	
Respiratory or skin sensitisation (Resp. Sens. 1)	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
Causes skin irritation.		
May cause an allergic skin reaction.		
Causes serious eye irritation.		
Harmful if inhaled.		
May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
May cause respiratory irritation.		
Suspected of causing cancer.		
May cause damage to organs through prolonged or repeated exposure.		
-	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer.	

16.6. Training advice

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2023 Print date: 15 Feb 2024 Version: 3

Page 13/13

PU Fix white 50ml (Comp. B)

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

