according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 1/12



Safe Clean NSF 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Safe Clean NSF 500ml

Article No.:

T204101

UFI:

9A23-02K1-ET0H-NXP6

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Cold cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS02 Flame



GHS07 Exclamation mark



GHS09 Environment

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 2/12



Safe Clean NSF 500ml

Hazard components for labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; propan-2-ol

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	

Hazard statements for health hazards		
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	

Hazard statements for environmental hazards		
H411	Toxic to aquatic life with long lasting effects.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves and eye protection/face protection.	

Precautionary statements Response		
P302 + P352	IF ON SKIN: Wash with plenty of water and soap.	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P312	Call a POISON CENTER if you feel unwell.	

Precautionary statements Storage		
P403	Store in a well-ventilated place.	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	

Precautionary statements Disposal		
P501	Dispose of contents/container to an appropriate recycling or disposal facility.	

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 921-024-6 REACH No.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	75 - < 100 Vol-%
		≥ 30 Vol-%

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 3/12



Safe Clean NSF 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	2.5 - < 10 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	carbon dioxide Substance with a community workplace exposure limit.	2.5 - < 10 Vol-%

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

Wash with plenty of water and soap.

After eve contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 4/12



Safe Clean NSF 500ml

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	② 10,000 ppm (18,000 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)

8.1.2. Biological limit values

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 5/12



Safe Clean NSF 500ml

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	2,035 mg/m ³	DNEL worker Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	608 mg/m ³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	773 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	300 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	DNEL Consumer Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	DNEL Consumer Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	DNEL worker Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	DNEL Consumer Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 6/12



Safe Clean NSF 500ml

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment





Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: \geq 0,5 mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to. Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol **Colour:** According to product designation

Odour: characteristic

Safety relevant basis data

variety relevant basis adda					
Parameter	Value	at °C	① Method		
			② Remark		
На	not applicable		② Mixture is not polar/aprotic.		
Initial boiling point and boiling range	82 °C		② propan-2-ol		
Flash point	-9 °C				
Evaporation rate	No data available				
Auto-ignition temperature	> 200 °C				

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 7/12



Safe Clean NSF 500ml

Parameter	Value	at °C	① Method ② Remark
Upper/lower flammability or explosive limits	0.8 - 12 Vol-%		
Vapour pressure	5,500 hPa	20 °C	
Density	0.72 g/cm³	20 °C	
Bulk density	not applicable		
Water solubility			② Not miscible or only slightly miscible.
Kinematic viscosity	20.5 mm ² /s	40 °C	

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

9.2.1. Information with regard to physical hazard classes

Explosives:

Not applicable

Flammable gases:

Not applicable

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

Oxidizing gases:

Not applicable

Gases under pressure:

Not applicable

Flammable liquids:

Not applicable

Flammable solids:

Not applicable

Self-reactive substances and mixtures:

Not applicable

Pyrophoric liquids:

Not applicable

Pyrophoric solids:

Not applicable

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

Oxidizing liquids:

Not applicable

Oxidizing solids:

Not applicable

Organic peroxides:

Not applicable

Corrosive to metals:

Not applicable

Desensitised explosives:

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 8/12



Safe Clean NSF 500ml

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 **LD**₅₀ **oral:** >2,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rat)

LC A sector link a letter to delite (see a) a 25

LC₅₀ Acute inhalation toxicity (gas): >25 ppmV (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L (Rat)

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

ATE (inhalation, vapour): 259,354 mg/L

LD₅₀ oral: ≥5,000 mg/kg (Ratte)

LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)

 LC_{50} Acute inhalation toxicity (dust/mist): \geq 50 mg/L 4 h (Ratte)

LD₅₀ oral: >5,000 mg/kg (Rat) OECD 401

LD₅₀ dermal: >2,920 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat) OECD 403

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 9/12



Safe Clean NSF 500ml

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 **LC₅₀:** 9,640 mg/L 4 d (fish, Pimephales promelas)

LC₅₀: >1,000 mg/L 4 d (fish)

EC₅₀: >100 mg/L (Algae/water plant)

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)

EC₅₀: >1,000 mg/L 2 d (crustaceans)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

LC₅₀: 8,970 mg/L 2 d (fish, Leuciscus idus (golden orfe))

LC₅₀: 11.4 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203

EC₅₀: 3 mg/L 2 d (crustaceans, Daphnia magna) OECD 202

NOEC: 0.17 mg/L 21 d (crustaceans, Daphnia magna)

LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)

EC₅₀: 30 - 100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

Aquatic toxicity:

No further relevant information available.

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6

Log Kow: 5.2

Bioconcentration factor (BCF): 250

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: -

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

Results of PBT and vPvB assessment: —

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 10/12



Safe Clean NSF 500ml

Aliphatic hydrocarbons	
Results of PBT and vPvB assessment: —	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC No.: 921-024-6
Results of PBT and vPvB assessment: —	

The product does not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Toxic to fish.

Toxic to aquatic life.

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Directive 2008/98/EC (Waste Framework Directive)

	, , ,	
HP 3	Flammable	
HP 4	Irritant — skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 14	Ecotoxic	

Waste code packaging

_ · · · · · · · · · · · · · · · · · · ·			
15 01 04	metallic packaging		

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)	
L4.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper ship	ping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	
14.3. Transport haza	rd class(es)			
•		***		
2.1	2.1	2.1	2.1	
14.4. Packing group		,		
		-		
14.5. Environmental hazards				
No	No	No	No	
14.6. Special precautions for user				
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L	Special Provisions: 63 190 277 327 344 381 959	Special Provisions: A145 A167 Limited quantity (LQ): Y203	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 11/12



Safe Clean NSF 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Excepted Quantities (EQ): E0	Excepted Quantities (EQ): F0	Limited quantity (LQ): Siehe SV277	Excepted Quantities (EQ): E0
Classification code:	Classification code:	Excepted Quantities (EQ): E0	Remark: Attention: Gases
Tunnel restriction code: (D)	Remark: Attention: Gases	EmS-No.: F-D, S-U	
Remark: Attention: Gases		Remark: Attention: Gases	

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Other regulations (EU):

Hazard categories:

- ullet P3b 'Flammable' aerosols Category 1 or 2, not containing flammable gases Category 1 or 2 nor flammable liquids Category 1
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 694.8 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

en / AT

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Mar 2023 Print date: 15 Feb 2024

Version: 3 Page 12/12



Safe Clean NSF 500ml

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DNEL derived no-effect level EC₅₀ Effective Concentration 50%

EN European Standard ES Exposure scenario

EWC European Waste Catalogue

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NOEC No Observed Effect Concentration

OSHA Occupational Safety & Health Administration persistent and bioaccumulative and toxic

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds ZNS central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

No data available

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.