

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 1/12



Techno Solv Eco 215I

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Techno Solv Eco 215I

Article No.:

T110235

UFI:

RENF-XFJA-F48T-JCME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Solvent mixture for removing adhesives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1B</i>)	H317: May cause an allergic skin reaction.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3



Page 2/12

Techno Solv Eco 215I

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS08
Health hazard



GHS09
Environment



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for health hazards

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Supplemental hazard information: none

Precautionary statements Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ .

Precautionary statements Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .
P331	Do NOT induce vomiting.
P391	Collect spillage.

Additional information:

Contains: (R)-P-menthadiene-1,8, C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch

2.3. Other hazards

Other adverse effects:

Based on the available information, the product does not contain any PBT or vPvB substances in content percentages $\geq 0.1\%$.

The product does not contain any substances with endocrine-disrupting properties in concentrations of $\geq 0.1\%$.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 3/12



Techno Solv Eco 215I

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 927-285-2 REACH No.: 01-2119480162-45	C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch Asp. Tox. 1 (H304), EUH066 Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) 5,000 mg/L	50 - ≤ 54 weight-%
CAS No.: 111-76-2 EC No.: 203-905-0 Index No.: 603-014-00-0 REACH No.: 01-2119475108-36	2-butoxyethanol Acute Tox. 4 (H302, H332), Eye Irrit. 2 (H319), Skin Irrit. 2 (H315) Warning Acute Toxicity Estimate ATE (oral) 300 mg/kg ATE (dermal) 2,000 mg/kg ATE (inhalation, vapour) 2.2 mg/L	30 - ≤ 32.5 weight-%
CAS No.: 5989-27-5 EC No.: 227-813-5 Index No.: 601-096-00-2	(R)-p-mentha-1,8-diene Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1B (H317) Danger M-factor (acute): 1 M-factor (chronic): 1	19.5 - ≤ 21 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

The person concerned shall be carried outside, away from the scene of the accident. If breathing stops, artificial respiration shall be given. A doctor must be consulted immediately.

In case of skin contact:

Soiled, soaked clothing must be taken off. One must take a shower immediately. A doctor must be consulted immediately. Take off contaminated clothing and wash it before reuse.

After eye contact:

Any contact lenses must be removed. One must immediately and extensively wash with water for at least 15 minutes, opening the eyelids well. Consult a doctor if symptoms persist.

Following ingestion:

A doctor must be consulted immediately. Do NOT induce vomiting. No medicine may be administered that has not been prescribed by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

There is no known specific information on symptoms and effects caused by this product.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide Foam, Powder-, Water mist

Unsuitable extinguishing media:

Nothing special.

5.2. Special hazards arising from the substance or mixture

In case of fire: Avoid inhalation of combustion products.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 4/12



Techno Solv Eco 215I

5.3. Advice for firefighters

The containers shall be cooled with water jets to prevent the decomposition of the product and the formation of potentially harmful substances. Complete fire protective clothing shall be worn at all times. Extinguishing water that is not allowed to enter the sewage pipes shall be collected. The water used for extinguishing and the fire residues shall be taken up in accordance with the regulations in force.

Personal protection: Normal firefighting clothing, e.g. an open-circuit compressed air respirator (EN 137) firefighting kit (EN469), firefighting gloves (EN 659) and firefighting boots (HO A 29 or A30)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

The leakage may be blocked if there is no danger. Appropriate protective devices (including personal protective devices as per para. 8 from the safety instructions) shall be put on to prevent contamination of skin, eyes and personal clothing. These instructions apply to both reprocessing supervisors and emergency stop interventions.

6.1.2. For emergency responders

Personal protection equipment:

Normal firefighting clothing, e.g. an open-circuit compressed air respirator (EN 137) firefighting kit (EN469), firefighting gloves (EN 659) and firefighting boots (HO A 29 or A30)

6.2. Environmental precautions

Prevent the product from entering waste water, surface water, ground water.

6.3. Methods and material for containment and cleaning up

Other information:

The spilled product must be sucked into a suitable container. The container to be used shall be tested for compatibility with the product, subject to section 10. The residual product shall be absorbed with inert absorbent material. Adequate ventilation of the affected area shall be provided. Contaminated material must be disposed of in accordance with the regulations in section 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Keep away from heat, sparks and free flame, refrain from smoking and use of matches or lighters. Without the necessary ventilation, vapours may accumulate in the lower layers near the floor and may also ignite remotely with the risk of flashback. Accumulation of electrostatic charges must be avoided. Eating, drinking and smoking are prohibited during product use. Wetted clothing and protective devices must be removed before entering the eating area. Avoid dispersal of the product in the environment.

7.2. Conditions for safe storage, including any incompatibilities

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Store only in original containers. It must be stored in a cool and well-ventilated place, away from heat sources, free flame, sparks and other sources of ignition. The containers must be kept away from any incompatible materials, whereby reference must be made to section 10.

7.3. Specific end use(s)

Recommendation:

Data not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3



Page 5/12

Techno Solv Eco 215I

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	② 40 ppm (200 mg/m ³) ⑤ (max. 4x30 min./Schicht, kann über die Haut aufgenommen werden) H
IOELV (EU)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	① 20 ppm (98 mg/m ³) ② 50 ppm (246 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	① 20 ppm (98 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	98 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	59 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	1,091 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	426 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	147 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	10.3 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	26.7 mg/kg bw/day	① DNEL Consumer ② Acute - dermal, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	6.3 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	8.8 mg/L	① PNEC aquatic, marine water
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	463 mg/L	① PNEC sewage treatment plant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3



Page 6/12

Techno Solv Eco 215I

Substance name	PNEC Value	① PNEC type
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	0.88 mg/L	① PNEC sediment, freshwater
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	3.46 mg/L	① PNEC sediment, marine water
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	8.14 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

The use of penetration-proof goggles is recommended (ref. standard EN 166).

Skin protection:

Hand protection: The hands must be protected with category III work gloves (ref. standard EN 374). For the final choice of material for the work gloves, the following aspects must be included: Compatibility, degradation, breaking time and permeability. In the case of preparations, the work glove resistance to chemical agents must be tested before use, as it is unpredictable. Glove wear time is conditioned by exposure time and modes of use.

Skin protection: Work clothing with long sleeves and category II accident protection shoes must be worn (see Regulation 2016/425 and standard EN ISO 20344). After taking off the protective clothing, one must wash with soap and water.

Respiratory protection:

If the threshold value (e.g. TLV-TWA) of the substance or one or more substances contained in the product is exceeded, it is advisable to wear a mask with a type A filter, the class of which (1, 2 or 3) should be selected according to the highest concentration used. (Ref. standard EN 14387). In the presence of gases or vapours of a different nature and/or gases or vapours containing particles (aerosol, smoke, mist, etc.), use combined filters. If the technical measures taken are not sufficient to reduce the exposure of the worker to the thresholds considered, the use of respiratory protective devices is necessary. The protection provided by the mask is limited in any case.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

Other protection measures:

Considering that appropriate protective measures should always take precedence over personal protective clothing, ensure that the workplace is well ventilated by effective local exhaust ventilation. For the selection of personal protective equipment, the trusted chemical manufacturers may need to be consulted. The personal protective equipment must be CE marked to indicate its suitability for the applicable regulations.

Emergency stop showers with face-eye-rinsing are to be provided.

8.2.3. Environmental exposure controls

Emissions from manufacturing processes, including those from ventilation equipment, should be checked for compliance with environmental legislation. Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: colourless

Odour: characteristic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 7/12



Techno Solv Eco 215I

Safety relevant basis data

Parameter	Value	① Method ② Remark
pH	No data available	
Melting point	No data available	
Freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	> 62 °C	
Evaporation rate	No data available	
Auto-ignition temperature	No data available	
Upper/lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Density	0.83 mg/L	
Bulk density	not applicable	
Water solubility	practically insoluble	
Dynamic viscosity	No data available	
Kinematic viscosity	No data available	

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No special reaction hazards with other substances under normal conditions of use.

Butyl glycol: Decomposes under the influence of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Butyl glycol: May react dangerously with: Aluminium, Oxidizing agent Forms peroxides with: Air.

10.4. Conditions to avoid

Avoid heating. Accumulation of electrostatic charges must be avoided. Keep away from sources of ignition - No smoking.

Butyl glycol: Avoid exposure to: Heat sources, open flames

10.5. Incompatible materials

Data not available.

10.6. Hazardous decomposition products

Vapours potentially hazardous to health may be formed by thermal decomposition or in case of fire.

Butyl glycol: Can develop: Hydrogen

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch	EC No.: 927-285-2
LD₅₀ oral: >2,000 mg/kg (Ratte) OECD TG	
LD₅₀ dermal: >2,000 mg/kg (Kaninchen)	
LC₅₀ Acute inhalation toxicity (vapour): 5,000 mg/L 4 h (Ratte) OCSE 4030	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 8/12



Techno Solv Eco 215I

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0
--

LD₅₀ oral: 300 mg/kg (Kaninchen)
--

LD₅₀ dermal: 2,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): 2.2 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

toxic

11.2. Information on other hazards

Other information:

According to the available data, the product does not contain any substances included in the main European lists of potential or suspected endocrine disruptors with effects on human health to be assessed.

SECTION 12: Ecological information

12.1. Toxicity

C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch EC No.: 927-285-2
--

LC₅₀: >1,000 mg/L 4 d (fish, <i>Oncorhynchus mykiss</i>)

EC₅₀: >1,000 mg/L 2 d (crustaceans, <i>Daphnia magna</i>)
--

EC₅₀: >1,000 mg/L 3 d (Algae/water plant, <i>Pseudokirchneriella subcapitata</i>)
--

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0
--

LC₅₀: 1,490 mg/L (fish, <i>Lepomis macrochirus</i>)
--

LC₅₀: 1,464 mg/L 4 d (fish, <i>Oncorhynchus mykiss</i>)
--

EC₅₀: 911 mg/L 3 d (Algae/water plant, <i>Pseudokirchneriella subcapitata</i>)

EC₅₀: 1,800 mg/L 2 d (crustaceans, <i>Daphnia magna</i>)

NOEC: 88 mg/L (Algae/water plant, <i>Pseudokirchneriella subcapitata</i>)

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5
--

LC₅₀: 35 mg/L 4 d (fish, <i>Oncorhynchus mykiss</i>)

EC₅₀: 69.6 mg/L 2 d (crustaceans, <i>Daphnia pulex</i>)
--

Aquatic toxicity:

The product must be considered environmentally hazardous and is toxic to aquatic life. In the long term, it can cause negative effects in the aquatic environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 9/12



Techno Solv Eco 215I

12.2. Persistence and degradability

C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch	EC No.: 927-285-2
Biodegradation: Yes, rapidly	
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0
Biodegradation: Yes, rapidly	
Remark: 1000 - 10000 mg/L	
(R)-p-mentha-1,8-diene	CAS No.: 5989-27-5 EC No.: 227-813-5
Biodegradation: Yes, rapidly	
Remark: 0,1 - 100 mg/L	

12.3. Bioaccumulative potential

2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0
Log K_{OW}: 0.81	
(R)-p-mentha-1,8-diene	CAS No.: 5989-27-5 EC No.: 227-813-5
Log K_{OW}: 4.38	
Bioconcentration factor (BCF): 1,022	

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

C11-14 zyklische Isoalkan- Kohlenwasserstoffe < 2 % aromatisch	EC No.: 927-285-2
Results of PBT and vPvB assessment: —	
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0
Results of PBT and vPvB assessment: —	
(R)-p-mentha-1,8-diene	CAS No.: 5989-27-5 EC No.: 227-813-5
Results of PBT and vPvB assessment: —	

Based on the available information, the product does not contain any PBT or vPvB substances in content percentages $\geq 0.1\%$.

12.6. Endocrine disrupting properties

According to the available data, the product does not contain any substances included in the main European lists of potential or suspected endocrine disruptors with effects on human health to be assessed.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Reuse if possible. Product residues are to be considered as hazardous waste. The hazardousness of the waste partially containing this product must be evaluated on the basis of the legal provisions in force. Disposal must be entrusted to a company authorised for waste management, taking into account national and, where applicable, local regulations.
The transport of the waste may be subject to ADR.

Waste treatment options

Appropriate disposal / Package:

Contaminated packaging material must be sent for recycling or disposal in accordance with the country's waste management regulations.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 3082	UN 3082	UN 3082	UN 3082

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024







Print date: 23 May 2024

Version: 3

Page 10/12



Techno Solv Eco 215I

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es)			
 9	No data available	 9	 9
14.4. Packing group			
III		III	III
14.5. Environmental hazards			
	No data available	 MARINE POLLUTANT	
14.6. Special precautions for user			
Limited quantity (LQ): 5L Hazard identification number (Kemler No.): 90 Classification code: -	No data available	Limited quantity (LQ): 5L EmS-No.: F-A, S-F	Special Provisions: A97, A158, A197, A215 Limited quantity (LQ): 450L Remark: Packaging details 964

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Seveso category - Directive 2012/18/EU: E2

Restrictions on the product or substances according to Annex XVII Regulation (EC) 1907/2006:

Product point 3-40

Substances contained point 75

Regulation (EU) 2019/1148 (marketing and use of explosives precursors): not applicable

Substances according to Candidate List (Art. 59 REACH): Based on the available information, the product does not contain SVHC substances in percentages $\geq 0.1\%$.

Substances subject to authorisation (Annex XIV REACH): none

Substances subject to export notification Regulation (EU) 649/2012: none

Substances subject to the Rotterdam Convention: none

P:302e7a5b-6f05-46cb-b218-145d1a3f5b6c none

Preventive medical check-ups: No precautionary examinations are required when working with this product. This is only on condition that the results of the risk assessment prove that there is only a moderate risk to the safety and health of workers and that the measures provided for by Directive 98/24/EC are sufficient to limit the risk.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 weight-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 11/12



Techno Solv Eco 215I

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1B</i>)	H317: May cause an allergic skin reaction.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	
Acute toxicity (inhalative) (<i>Acute Tox. 4</i>)	H332: Harmful if inhaled.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 15 May 2024

Print date: 23 May 2024

Version: 3

Page 12/12



Techno Solv Eco 215I

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available