according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2

Page 1/9



Multi Paste 250g

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Multi Paste 250g

Article No.:

T479002

UFI:

1X8X-RE42-382X-AFFH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
STOT-repeated exposure (STOT RE 1)	H372: Causes damage to organs through prolonged or repeated exposure. ()	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS08 Health hazard



GHS07
Exclamation mark

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024

Print date: 4 Jun 2024 Version: 2

Page 2/9



Multi Paste 250g

Hazard components for labelling:

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%)

Hazard statements for health hazards			
H336	May cause drowsiness or dizziness.		
H372 Causes damage to organs through prolonged or repeated exposure. ()			

Hazard statements for environmental hazards		
H412	Harmful to aquatic life with long lasting effects.	

Supplemental hazard information: none

Precautionary statements Prevention		
P264	Wash hands thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	

Precautionary statements Response		
P312	Call a POISON CENTER/doctor/ if you feel unwell.	

Precautionary statements Storage		
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statements Disposal		
P501	Dispose of contents/container to an appropriate recycling or disposal facility.	

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name	Concentration
	Classification according to Regulation (EC) No 1272/2008 [CLP]	
CAS No.: 64742-82-1 EC No.: 919-446-0 REACH No.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%) Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT RE 1 (H372), STOT SE 3 (H336)	24.5 weight-%
CAS No.: 102-71-6 EC No.: 203-049-8 REACH No.: 01-2119486482-31	Triäthanolamin The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Acute Toxicity Estimate ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) ≥ 50 mg/L	1.509 weight-%
CAS No.: 1336-21-6 EC No.: 215-647-6 Index No.: 007-001-01-2 REACH No.: 01-2119488876-14	ammonia, aqueous solution Aquatic Acute 1 (H400), Eye Dam. 1 (H318), Skin Corr. 1B (H314) Danger Specific concentration limit (SCL) STOT SE 3; H335: C ≥ 5% Acute Toxicity Estimate ATE (oral) 350 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) ≥ 50 mg/L	0.915 weight-%

Full text of H- and EUH-phrases: see section 16.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2

Page 3/9



Multi Paste 250g

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Always seek medical advice as soon as possible in case of serious or persistent disorders.

Following inhalation:

In case of serious or persistent disorders: Move to fresh air, ensure rest and consult a doctor.

In case of skin contact:

flush with water

After eye contact:

First rinse with plenty of water, then consult a doctor if necessary.

Following ingestion:

First rinse with plenty of water, then consult a doctor if necessary.

4.2. Most important symptoms and effects, both acute and delayed

Dermal Eye contact Redness oral Diarrhea Headache Abdominal cramps Fatigue Vomiting inhalation Sore throat Cough

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2, Powder, Foam, Water

Unsuitable extinguishing media:

none

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for firefighters

No data available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Do not step in or touch spilled substances and avoid inhalation of fumes, smoke, dust and vapours by staying on the side facing the wind. Remove contaminated clothing and used contaminated protective equipment and dispose of safely.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Allow to be absorbed by absorbent material.

6.4. Reference to other sections

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2 Page 4/9



Multi Paste 250g

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Handle with care to avoid spillage.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Store in a well-sealed container in a closed, frost-free and ventilated room.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%) CAS No.: 64742-82-1 EC No.: 919-446-0	 20 mL/m³ 40 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von mehr als 25 %)
MAK (AT)	Hydrocarbons, C9-C12, n-alkanes, iso- alkanes, cyclic, aromatics (2-25%) CAS No.: 64742-82-1 EC No.: 919-446-0	 ① 70 mL/m³ ② 140 mL/m³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von 1 % bis 25 % und an Hexanen von weniger als 1 %)
MAK (AT)	Triäthanolamin CAS No.: 102-71-6 EC No.: 203-049-8	① 0.8 ppm (5 mg/m³) ⑤ (einatembare Fraktion) S
MAK (AT)	Triäthanolamin CAS No.: 102-71-6 EC No.: 203-049-8	② 1.6 ppm (10 mg/m³) ⑤ (einatembare Fraktion, max. 4x15 min./Schicht) S

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

The level of protection and types of controls required will depend on the potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. Further information can be found in section 7 of the safety data sheet.

8.2.2. Personal protection equipment









according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2 Page 5/9



Multi Paste 250g

Eye/face protection:

Keep eye wash bottle within reach. Wear tight-fitting safety glasses. In case of exceptional processing problems, wear a face shield and protective suit.

Skin protection:

Handle with nitrile protective gloves. Breakthrough time: > 480 min., layer thickness: 0.35 mm, according to EN 374. Check gloves carefully before use. Remove gloves carefully without touching the outside with the bare hand. Suitability for a specific workplace must be discussed with the manufacturer of the protective gloves. Wash and dry the hands.

Respiratory protection:

Use with adequate exhaust ventilation. If breathing hazards are present, use an air-purifying face mask if necessary. For protection against these stressful levels, use type ABEK.

Other protection measures:

Impermeable clothing. The type of protective equipment depends on the concentration and quantity of hazardous substances in the workplace concerned.

8.2.3. Environmental exposure controls

Comply with applicable environmental regulations that limit releases to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions. For more information, see sections 6 and 13 of the safety data sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: pink

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
pH	8.3		
Melting point	0 °C		
Freezing point	No data available		
Initial boiling point and boiling range	100 - 192 °C		
Flash point	63 °C		
Evaporation rate	No data available		
Auto-ignition temperature	260 °C		
Upper/lower flammability or explosive limits	0.7 - 6 %		
Vapour pressure	2,332 Pa	20 °C	
Vapour density	No data available		
Density	No data available		
Relative density	1.24	20 °C	
Bulk density	not applicable		
Water solubility	practically insoluble		
Dynamic viscosity	No data available		
Kinematic viscosity	8,065 mm²/s	40 °C	

9.2. Other information

Dynamic viscosity, 20 °C: 10.000 mPa.s Evaporation rate (n-BuAc =1): 0,300 Volatile organic compounds (VOC): 24,50 % Volatile organic compounds (VOC): 303,800 g/l

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2 Page 6/9



Multi Paste 250g

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Protect from sunlight. Do no expose to temperatures exceeding 50 °C.

10.5. Incompatible materials

Keep away from: Acids

10.6. Hazardous decomposition products

No decomposition during normal use

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatics (2-25%) CAS No.: 64742-82-1

EC No.: 919-446-0

LD₅₀ oral: 2,000 mg/kg (Rat)

LD₅₀ dermal: ≥5,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)

Triäthanolamin CAS No.: 102-71-6 EC No.: 203-049-8

LD₅₀ oral: ≥5,000 mg/kg (Ratte)

LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Ratte)

ammonia, aqueous solution CAS No.: 1336-21-6 EC No.: 215-647-6

LD₅₀ oral: 350 mg/kg (Rat)

LD₅₀ dermal: ≥5,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)

Acute oral toxicity:

> 2.000 mg/kg

Acute dermal toxicity:

> 2.000 mg/kg

STOT-single exposure:

H336 STOT SE 3: May cause drowsiness or dizziness.

STOT-repeated exposure:

H372 STOT RE 1: Causes damage to organs through prolonged or repeated exposure.

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

ammonia, aqueous solution CAS No.: 1336-21-6 EC No.: 215-647-6

LC₅₀: 0.89 mg/L (fish)

EC₅₀: 110 mg/L (crustaceans, Daphnia)

12.2. Persistence and degradability

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024

Print date: 4 Jun 2024

Version: 2 Page 7/9



Multi Paste 250g

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

water hazard class (AwSV): 2 Water solubility: insoluble

12.5. Results of PBT and vPvB assessment

ammonia, aqueous solution CAS No.: 1336-21-6 EC No.: 215-647-6 Results of PBT and vPvB assessment: -

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not drain into the sewage system. Disposal must be carried out by an authorized service provider. Any restrictions imposed by the local authorities must always be observed.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft Sea transport (IMDG) (ADN)		Air transport (ICAO-TI / IATA-DGR)		
14.1. UN number or	L4.1. UN number or ID number				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.		
14.2. UN proper ship	ping name				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.		
14.3. Transport haza	rd class(es)				
not relevant	not relevant	not relevant	not relevant		
14.4. Packing group		`			
not relevant	not relevant	not relevant	not relevant		
14.5. Environmental hazards					
not relevant	not relevant	not relevant	not relevant		
14.6. Special precau	14.6. Special precautions for user				
not relevant	not relevant	not relevant	not relevant		

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 303.8 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2 Page 8/9



Multi Paste 250g

SECTION 16: Other information

16.1. Indication of changes

Section 3: Composition/Information on Ingredients

16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DNEL derived no-effect level EC₅₀ Effective Concentration 50%

EINECS European Inventory of Existing Commercial Chemical Substances

EN European Standard ES Exposure scenario

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization
LC50 Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

SCL Specific concentration limit

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

ATE: Acute Toxicity Estimate

Nr.: Number

UFI: Unique Formula Identifier WGK: water hazard class

WGK 1: slightly hazardous to water

WGK 2: hazardous to water

WGK 3: highly hazardous to water

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
	H372: Causes damage to organs through prolonged or repeated exposure. ()	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 29 May 2024 Print date: 4 Jun 2024

Version: 2 Page 9/9



Multi Paste 250g

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15 $\,$

Hazard statements	
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information