

# MT6

## MULTIPURPOSE RELEASE AGENT

- Super Fast acting
- Lubricant
- Anticorrosion
- Protectant
- Release Fluid
- Water-repellent - Anti Humidity
- Cleaning Fluid
- 360° Application
- Rubbers and Plastics
- Metals
- Textiles
- Painted Surfaces



### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# MULTI TECH 6

## General Information

MULTI TECH 6 comprises four products in one: lubricant - protectant - release fluid - water-repellent - anticorrosion - anti-humidity - cleaning fluid.

## Technical Information

### AEROSOL

Physical state: Aerosol  
 Colour: brown  
 Odour: sweetish  
 Initial boiling point: -40°C  
 Flash point: -80°C  
 Upper/lower flammability or explosive limits: 0.6 - 15 Vol-%  
 Density (at 20°C): 0,783 g/cm<sup>3</sup>  
 Kinematic viscosity: < 7 mm<sup>2</sup>/s  
 electric strength = 42 kV  
 Temperature resistance: - 30°C to +130°C





### LIQUID

Physical state: Liquid  
 Colour: light brown  
 Odour: vanilla  
 Initial boiling point: 110°C  
 Flash point: 30°C ISO 3679  
 Upper/lower flammability or explosive limits: 0.5 - 7 Vol-%  
 Density (bei 20°C): 0,788 g/cm<sup>3</sup>  
 Kinematic viscosity (at 40°C): < 7 mm<sup>2</sup>/s DIN EN ISO 3104  
 Electric strength: 42 kV

## Application and Use

- Lubricant - Anticorrosion - Protectant  
 The product forms a durable film that provides protection against water, frost, humidity and rust or oxidation: It protects metals and their microscopic imperfections.
- Release Fluid  
 Attacks rust and all other types of oxidation, facilitating the release of any locked, rusted or frozen component or mechanism.
- Water-repellent - Anti Humidity  
 Forms a protective film between the surface and the humidity.
- Cleaning Fluid  
 Its formula enables it to be used to clean all surfaces, eliminating grease and grime and preventing the formation of an oxidation layer.
- USE  
 Shake well before use (Aerosol) and apply product to surface to be treated, allow a contact time of 1 minute and proceed and carry out the required action. Eliminates rust and oxidation. Loosens blocked mechanical functions. Drives out moisture on electrical contacts.

Article nr	Name	Content	Shelf Life	Catalog
T206001	Multi Tech 6 500ml	500ml	see imprint + 36 months	LUBRICANTS
T206005	Multi Tech 6 5l	5l	see imprint + 36 months	LUBRICANTS



LUBRICANTS

WWW.TECH-MASTERS.EU

