according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 1/15

Power Clean 5

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

* **1.1. Product identifier** Trade name/designation:

Power Clean 51

Article No.: T499005 UFI: 24SW-49DF-1903-5TCX

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Cold cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 13 Nov 2024

Print date: 13 Nov 2024 Version: 4

Page 2/15

Power Clean 5


* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



Exclamation mark



Hazard components for labelling:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; propan-2-ol; Acetone

GHS08

Health hazard

GHS09

Environment

Hazard statements for physical hazards		
H225	Highly flammable liquid and vapour.	
Hazard statements for health hazards		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
Hazard statements for environmental hazards		

H411 Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
Precautionary statements Response		

Precautionary stat	Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P302 + P352	IF ON SKIN: Wash with plenty of water and soap.		
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P331	Do NOT induce vomiting.		

Precautionary statements Storage

Store in a well-ventilated place. Keep cool. P403 + P235

Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Additional information:

The product contains: Notifiable explosives precursors. Provision, transfer, possession and use in accordance with Regulation (EU) 2019/1148, Article 9.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 3/15

Power Clean 5

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

*

Cleaning agent

Additional information:

The application of a CRF (Child-Resist Fastening) is mandatory when this product is offered on the consumer market. Please note that the CRF is part of the packaging and not of the classification. The application of a TWD (Tactile Warning of Danger) is mandatory when this product is offered on the consumer market. Please note that the TWD is part of the packaging and not of the classification.

Hazardous ingredients / Hazardous impurities / Stabilisers:

r	gredients / Hazardous impurities / Stabilisers:				
Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration			
CAS No.: 64742-49-0 EC No.: 927-510-4 Index No.: 649-328-00-1 REACH No.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) 0 1 2 Danger Acute Toxicity Estimate ATE (oral) \ge 5,000 mg/kg ATE (dermal) > 2,920 mg/kg ATE (inhalation, vapour) > 23.3 mg/L	25 - 50 %			
EC No.: 921-024-6 REACH No.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexaneThe substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,920 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.2 mg/L	25 - 50 %			
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L	25 - 50 %			
	Aliphatic hydrocarbons The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	≥ 30 %			
CAS No.: 67-64-1 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	Acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) O Danger EUH066 Acute Toxicity Estimate ATE (oral) \geq 5,000 mg/kg ATE (dermal) $>$ 20 mg/kg ATE (inhalation, gases) $>$ 20 ppmV ATE (inhalation, vapour) $>$ 50 mg/L ATE (inhalation, dust/mist) 76 mg/L	10 - 25 %			

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 4/15

Power Clean 5

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

* 6.2. Environmental precautions

Do not allow to enter drains/surface water/ground water. Prevent penetration into sewers, pits and cellars In case of spillage into water or sewage system, inform the competent authorities.

* 6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation. Dispose of contaminated material as waste according to section 13.

6.4. Reference to other sections

Further information on proper storage: see section 7. For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace. Avoid aerosol formation.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 5/15

Power Clean 5

TECH MASTERS

Storage class (TRGS 510, Germany): 3 – Flammable liquids Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Keep container tightly closed.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	 200 mL/m³ 400 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	 170 mL/m³ 340 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	 2 800 ppm (2,000 mg/m³) (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	1 200 ppm (500 mg/m³)
MAK (AT)	Acetone CAS No.: 67-64-1	 2,000 ppm (4,800 mg/m³) (max. 4x15 min./Schicht)
IOELV (EU)	Acetone CAS No.: 67-64-1	① 500 ppm (1,210 mg/m³)
MAK (AT)	Acetone CAS No.: 67-64-1	① 500 ppm (1,200 mg/m³)

8.1.2. Biological limit values No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	 DNEL type Exposure route
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	2,085 mg/m³	 DNEL worker Long-term - inhalation, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	477 mg/m³	 DNEL Consumer Long-term - inhalation, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 6/15

Power Clean 5I

Substance name	DNEL value	1 DNEL type
		② Exposure route
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	300 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	2,035 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	608 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	day	 DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	day	 DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	day	 DNEL Consumer Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m³	 DNEL worker Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	 DNEL Consumer Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Acetone CAS No.: 67-64-1	1,210 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
Acetone CAS No.: 67-64-1	200 mg/m ³	DNEL Consumer DNEL Consumer Inhalation, systemic effects
Acetone CAS No.: 67-64-1	2,420 mg/m ³	DNEL worker Long-term – inhalation, local effects
Acetone CAS No.: 67-64-1	186 mg/kg bw/ day	 Long-term - dermal, systemic effects
Acetone CAS No.: 67-64-1	62 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 7/15

Power Clean 5I

Substance name	DNEL value	 DNEL type Exposure route
Acetone CAS No.: 67-64-1	62 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	${f 1}$ PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release
Acetone CAS No.: 67-64-1	10.6 mg/L	1 PNEC aquatic, freshwater
Acetone CAS No.: 67-64-1	1.06 mg/L	1 PNEC aquatic, marine water
Acetone CAS No.: 67-64-1	100 mg/L	① PNEC sewage treatment plant
Acetone CAS No.: 67-64-1	30.4 mg/L	① PNEC sediment, freshwater
Acetone CAS No.: 67-64-1	3.04 mg/L	① PNEC sediment, marine water
Acetone CAS No.: 67-64-1	29.5 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection: Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration. Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 8/15

Power Clean 5

NBR (Nitrile rubber)

Recommended material thickness: \geq 0,5 mm Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to. Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Odour: characteristic **Colour:** colourless **flammability:** No data available

Safety relevant basis data

Parameter	Value	at °C	 Method
			② Remark
рН	not applicable		② Mixture is not polar/aprotic.
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	55.8 - 56.6 °C		② Acetone
Flash point	< -18 °C		
Evaporation rate	No data available		
Auto-ignition temperature	> 200 °C		② Highly flammable
Upper/lower flammability or explosive limits	0.6 - 13 Vol-%		
Vapour pressure	246 hPa	20 °C	
Vapour density	No data available		
Density	0.72 g/cm ³	20 °C	
Bulk density	not applicable		
Water solubility	Immiscible		② Not miscible or only slightly miscible.
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

* 9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

Organic solvents: 100,0 %



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 9/15

*

Power Clean 5

Solid content: 0,0 %

9.2.1. Information with regard to physical hazard classes

Flammable liquids:

Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4

LD₅₀ oral: ≥5,000 mg/kg (Rat)

LD₅₀ dermal: >2,920 mg/kg (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >23.3 mg/L 4 h (Rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6

LD₅₀ oral: >5,000 mg/kg (Rat) OECD 401

LD₅₀ dermal: >2,920 mg/kg (Rabbit)

LC50 Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat) OECD 403

LC₅₀ Acute inhalation toxicity (vapour): >25.2 mg/L 4 h (Rat)

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

LD₅₀ oral: >2,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rat)

LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)

Acetone CAS No.: 67-64-1

LD₅₀ oral: ≥5,000 mg/kg (Rat)

LD₅₀ dermal: >20 mg/kg (Rat)

LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >50 mg/L 4 h (Rat)

LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 10/15

Power Clean 5

TECH MASTERS

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

* 12.1. Toxicity

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4	
LC₅₀: >13.4 mg/L 4 d (fish)	
EC₅₀: 3 mg/L (crustaceans, Daphnia magna))	
NOEC: 0.17 mg/L (Algae/water plant, Daphnia magna)	
LOEC: 0.32 mg/L (Algae/water plant)	
EC₅₀: 3 mg/L 2 d (Daphnia magna)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	
LC₅₀: 11.4 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203	
EC₅₀: 3 mg/L 2 d (crustaceans, Daphnia magna) OECD 202	
NOEC: 0.17 mg/L 21 d (crustaceans, Daphnia magna)	
LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)	
EC₅₀: 30 – 100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)	
LC₅₀: >1 – 10 mg/L 4 d (fish, Pimephales promelas)	
EC₅₀: >1 - 10 mg/L 2 d (crustaceans, Daphnia magna)	
NOEC: 2.045 mg/L 28 d (fish, Oncorhynchus mykiss)	
NOEC: 1 mg/L 21 d (crustaceans, Daphnia magna) OECD 211	
ErC₅₀: 10 – 30 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201	
LOEC: 0.32 mg/L 21 d (Daphnia magna)	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	
LC₅₀: >1,000 mg/L 4 d (fish)	
EC ₅₀ : >1,000 mg/L 2 d (crustaceans)	
LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas)	
LC₅₀: 9,714 mg/L 1 d (Daphnia magna)	
EC₅₀: >100 mg/L (Algae/water plant, Bacteria)	
LOEC: 1,000 mg/L (Alge)	
EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)	
ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)	
LOEC: 1,000 mg/L	
	en / A

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 11/15

Power Clean 5

Acetone CAS No.: 67-64-1

LC₅₀: 8,300 mg/L 4 d

LC₅₀: 5,540 mg/L 4 d (fish, Oncorhynchus mykiss)

LC₅₀: 4,042 mg/L (fish)

EC₅₀: 8,800 mg/L 2 d (crustaceans, Daphnia magna)

EC50: 8,300 mg/L (fish)

EC₅₀: 302 mg/L 4 d (Algae/water plant)

NOEC: 2,212 mg/L (crustaceans, Daphnia pulex)

Aquatic toxicity:

No further relevant information available.

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6

Biodegradation: Yes, rapidly

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Acetone CAS No.: 67-64-1

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6

Log K_{OW}: 5.2

Bioconcentration factor (BCF): 250

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

Acetone CAS No.: 67-64-1

Log K_{OW}: -0.23

Bioconcentration factor (BCF): 3

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 927-510-4

Results of PBT and vPvB assessment: -

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6

Results of PBT and vPvB assessment: -

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

Acetone CAS No.: 67-64-1

Results of PBT and vPvB assessment: -

Aliphatic hydrocarbons

Results of PBT and vPvB assessment: -

The product does not meet the PBT/vPvB criteria.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 12/15

Power Clean 5

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

* 12.7. Other adverse effects

Do not allow to enter drains/surface water/ground water. Drinking water hazard even when small quantities leak into the subsoil. Toxic to aquatic life. Toxic to fish. water hazard class 2: obviously hazardous to water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable	
HP 4	Irritant — skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 14	Ecotoxic	l

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

• • • •	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI) IATA-DGR)
14.1. UN number or l	D number	·	
UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper ship	ping name		
N.O.S. (HEPTANES, Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane)	FLAMMABLE LIQUID, N.O.S. (HEPTANES, Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane)	FLAMMABLE LIQUID, N.O.S. (HEPTANES, Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane)	FLAMMABLE LIQUID, N.O.S. (HEPTANES, Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cycl <5% n-hexane)
14.3. Transport haza	rd class(es)		
3	3	3	3
14.4. Packing group			
	11	11	Ш
14.5. Environmental	hazards		
×2	¥2		No
14.6. Special precaut	tions for user		
Special Provisions: 274 601 640C	Special Provisions: 274 601 640C	Special Provisions: 274	Special Provisions: A3
Limited quantity (LQ):	Limited quantity (LQ):	Limited quantity (LQ):	Limited quantity (LQ): Y341
	Excepted Quantities (EQ): E2	Excepted Quantities (EQ): E2	Excepted Quantities (EQ): E2



GeSi.de

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 13/15

Power Clean 5I

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Hazard identification number (Kemler No.): 33 Classification code: not determined Tunnel restriction code: (D/E) Remark: Caution: Flammable liquid substances! Maximum net quantity Inner packaging 30ml Maximum net quantity Outer packaging 500ml	Classification code: not determined Remark: Caution: Flammable liquid substances!	EmS-No.: F-E, S-E Remark: Caution: Flammable liquid substances! Congestion category B Maximum net quantity Inner packaging 30ml Maximum net quantity Outer packaging 500ml	Remark: Caution: Flammable liquid substances!

14.7. Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Seveso category: E2 Hazardous to the aquatic environment

P5c FLAMMABLE LIQUIDS

Quantity threshold (in tons) for use in lower class farms: 200t

Quantity threshold (in tons) for use in upper-tier establishments: 500t

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: acetone

Regulation (EC) No 273/2004 on drug precursors: Acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: Acetone

Other regulations (EU):

Hazard categories:

- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: Volatile organic compounds (VOC) content in percent by weight: 720 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4

Page 14/15

Power Clean 5I

SECTION 16: Other information

* 16.1. Indication of changes

10.1.1	nucation of changes
1.1.	Product identifier
2.2.	Label elements
3.2.	Mixtures
6.2.	Environmental precautions
6.3.	Methods and material for containment and cleaning up
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
9.2.	Other information
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.7.	Other adverse effects
14.3.	Transport hazard class(es)
14.6.	Special precautions for user
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
162 /	Abbreviations and acronyms
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level Effective Concentration 50%
EC ₅₀	
EN ES	European Standard Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association National Institute for Occupational Safety & Health
NIOSH NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	
RID TRGS	Dangerous goods regulations for transport by rail Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system
16.3.	Key literature references and sources for data
	a available



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Nov 2024 Print date: 13 Nov 2024 Version: 4



Page 15/15

Power Clean 5

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.