according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 1/13



Electro Cleaner 400ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Electro Cleaner 400ml

Article No.:

T402001

UFI:

9U8H-UC0D-EC25-X9U0

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Contact cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS02 Flame



GHS07 Exclamation mark



GHS09 Environment

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 2/13



Electro Cleaner 400ml

Hazard components for labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; propan-2-ol

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	

Hazard statements for health hazards		
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

Hazard statements for environmental hazards		
H411	Toxic to aquatic life with long lasting effects.	

Supplemental hazard information		
EUH066	Repeated exposure may cause skin dryness or cracking.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe spray.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear eye protection/face protection.	

Precautionary statements Response		
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statements Storage		
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	

2.3. Other hazards

Other adverse effects:

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 3/13



Electro Cleaner 400ml

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-49-0 EC No.: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger Acute Toxicity Estimate ATE (dermal) > 2,800 - 3,100 mg/kg ATE (inhalation, vapour) 23.3 mg/L	25 - < 50 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L	25 - < 50 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	carbon dioxide Substance with a community workplace exposure limit. Acute Toxicity Estimate ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) 259,354 mg/L ATE (inhalation, dust/mist) ≥ 50 mg/L	3 - < 5 Vol-%
CAS No.: 108-01-0 EC No.: 203-542-8	2-dimethylaminoethanol Acute Tox. 3 (H331), Acute Tox. 4 (H312, H302), Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335), Skin Corr. 1B (H314) Danger Acute Toxicity Estimate ATE (oral) 2,000 mg/kg ATE (dermal) 1,220 mg/kg ATE (inhalation, vapour) 3 mg/L ATE (inhalation, dust/mist) 0.5 mg/L	< 0.1 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact:

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur or persist, consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

Self-protection of the first aider:

First aider: Pay attention to self-protection!

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 4/13



Electro Cleaner 400ml

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, Fatigue, Skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Foam, Carbon dioxide (CO2), Extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely.

In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Pressurised container: May burst if heated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. First aider: Pay attention to self-protection!

Protective equipment:

Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

Personal protection equipment:

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clean contaminated articles and floor according to the environmental legislation.

Other information:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 5/13

Electro Cleaner 400ml



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advices on general occupational hygiene

Avoid exposure - obtain special instructions before use. Wear suitable work clothing. Draw up and observe skin protection programme. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Protect from frost. Protect from direct sunlight. Store in a cool dry place. The official regulations for the storage of pressurised gas packages must be observed.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	 1 200 mL/m³ 2 400 mL/m³ 5 (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	 170 mL/m³ 340 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 6/13



Electro Cleaner 400ml

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	② 10,000 ppm (18,000 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	2,035 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	608 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	773 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	699 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0	699 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m ³	① DNEL Consumer② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	DNEL worker Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 7/13



Electro Cleaner 400ml

Substance name		① DNEL type ② Exposure route
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

8.2.2. Personal protection equipment

Eve/face protection:

Suitable eye protection: Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Preventive skin protection through the use of skin protectants is recommended. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Glove material: NBR (Nitrile rubber)

Breakthrough time: 480 min

Thickness of the glove material: 0,45 mm

EN ISO 374

Body protection:

Wear suitable protective clothing when working. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

If the relevant occupational exposure limits are exceeded, the following must be observed: Suitable respiratory protective device: Combination filter device (DIN EN 141). Filter unit with filter or blower filter unit type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal rules and regulations.

8.2.3. Environmental exposure controls

Observe legal rules and regulations.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 8/13



Electro Cleaner 400ml

SECTION 9: Physical and chemical properties

st 9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol Colour: colourless

Odour: solvent-like flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	1 Method
			② Remark
Initial boiling point and boiling range	82 °C		
Flash point	1 °C		
Evaporation rate	No data available		
Upper/lower flammability or explosive limits	0.7 - 12 Vol-%		
Vapour pressure	No data available		
Density	0.7525 g/cm³	20 °C	① DIN 51757
Water solubility	No data available		

9.2. Other information

The data refer to the technical active substance: relative density, colour, odour, viscosity, pH-value.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharge.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

	•	• •	•
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	CAS No.: 64742-49-0	EC No.: 920-75	0-0
LD₅₀ dermal: >2,800 - 3,100 mg/kg (Rat)			
LC ₅₀ Acute inhalation toxicity (vapour): 23.3 mg/L 4	LC ₅₀ Acute inhalation toxicity (vapour): 23.3 mg/L 4 h (Rat) OECD 403		
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7			
LD₅₀ oral: >2,000 mg/kg (Rat)			
LD ₅₀ dermal: >2,000 mg/kg (Rat)			
LC ₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)			
LC ₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)			

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 9/13



Electro Cleaner 400ml

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

ATE (inhalation, vapour): 259,354 mg/L

LD₅₀ oral: ≥5,000 mg/kg (Ratte)

LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (dust/mist): ≥50 mg/L 4 h (Ratte)

2-dimethylaminoethanol CAS No.: 108-01-0 EC No.: 203-542-8

ATE (inhalation, vapour): 3 mg/L
ATE (inhalation, dust/mist): 0.5 mg/L

LD₅₀ oral: 2,000 mg/kg (Ratte)

LD₅₀ dermal: 1,220 mg/kg (Kaninchen)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eve damage/irritation:

Causes serious eve irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 12: Ecological information

* 12.1. Toxicity

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0

EC₅₀: 7.4 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 0.574 mg/L 28 d (fish, Oncorhynchus mykiss) OECD 202

NOEC: 1 mg/L 21 d (Algae/water plant, Daphnia magna)

ErC₅₀: 12 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 10/13



Electro Cleaner 400ml

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

LC₅₀: >1,000 mg/L 4 d (fish)

EC₅₀: >1,000 mg/L 2 d (crustaceans)

LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC₅₀: 9,714 mg/L 1 d (Daphnia magna)

EC₅₀: >100 mg/L (Algae/water plant, Bacteria)

LOEC: 1,000 mg/L (Alge)

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Abiotic degradation:

No further relevant information available.

Additional information:

AOX (mg/l): 0

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics CAS No.: 64742-49-0 EC No.: 920-750-0

Results of PBT and vPvB assessment: —

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

Results of PBT and vPvB assessment: —

2-dimethylaminoethanol CAS No.: 108-01-0 EC No.: 203-542-8

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 11/13



Electro Cleaner 400ml

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

16 05 04 * Gases in pressure containers (including halons) containing hazardous substances

*: Evidence for disposal must be provided.

Waste code packaging

15 01 04 metallic packaging

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shi	oping name	•	-
AEROSOLS	AEROSOLS	AEROSOLS flammable (Hydrocarbons C7-C9, n- alkanes, iso-alkanes, cyclics)	AEROSOLS flammable
14.3. Transport haza	ard class(es)		
2.1	2.1	2.1	2.1
14.4. Packing group			
		-	
14.5. Environmenta	hazards		
¥2>	¥2	MARINE POLLUTANT	¥2
14.6. Special precau	itions for user		
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D)	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): 1000 mL Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U	Special Provisions: A145 A167 A802 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: IATA Packing Instructions Passenger: 203 IATA Maximum Quantity - Passenger: 75 kg IATA- Verpackungsanweisung - Cargo: 203 IATA Maximum Quantity - Cargo: 150 kg

14.7. Maritime transport in bulk according to IMO instruments

not applicable

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 12/13



Electro Cleaner 400ml

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 28, Entry 40, Entry 75

15.1.2. National regulations

No data available

TRGS

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

Technische Regeln für Gefahrstoffe

SECTION 16: Other information

16.1. Indication of changes

3.2.	Mixtures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
14.3.	Transport hazard class(es)
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

10.2.	tobreviations and deronyms
16.2. Al	obreviations and acronyms
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AOX	Adsorbable Organic halogen compounds
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 14 Jan 2025 Print date: 24 Jan 2025

Version: 3 Page 13/13



Electro Cleaner 400ml

UN United Nations

ZNS central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage.	
H331	Toxic if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.