SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 10 Mar 2025
Print date: 19 Mar 2025
Version: 4

Fast Clean 600ml

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier

Trade name/designation:

Fast Clean 600ml

Article No.:
T497001

UFI:
QD1C-6R37-7D52-ANUP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:
Cleaning agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH
Hartleitnerstraße 3
4653 Eberstalzell
Austria
Telephone: +43 (0) 7241 213 79
E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters *(Aerosol 1)*	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard *(Asp. Tox. 1)*	H304: May be fatal if swallowed and enters airways.	
STOT-single exposure *(STOT SE 3)*	H336: May cause drowsiness or dizziness.	
Skin corrosion/irritation *(Skin Irrit. 2)*	H315: Causes skin irritation.	
Hazardous to the aquatic environment *(Aquatic Chronic 2)*	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:

GHS02
Flame

GHS07
Exclamation mark

GHS09
Environment

Signal word: Danger

Hazard components for labelling:
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements for physical hazards	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards	
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Hazard statements for environmental hazards	
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.

Precautionary statements Response	
P301 + P312	IF SWALLOWED: Call a doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of water and soap.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.

Precautionary statements Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Other adverse effects:
This mixture does not contain substances classified as PBT or vPvB substances.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.
In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

*
3.2. Mixtures

Additional information:
Labelling for contents according to regulation (EC) No. 648/2004:
>= 30% aliphatic hydrocarbons

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 921-024-6 REACH No.: 01-2119475514-35	**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane** Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315)  Danger **Acute Toxicity Estimate** ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,920 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.2 mg/L	50 – < 100 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	**carbon dioxide** Press. Gas (Liq.) (H280)  Warning **Acute Toxicity Estimate** ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) 259,354 mg/L ATE (inhalation, dust/mist) ≥ 50 mg/L	3 – < 5 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:
IF INHALED: Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact:
Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After eye contact:
Rinse cautiously with water for several minutes. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion:
Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

Self-protection of the first aider:
Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed
Headache, Nausea, Dizziness, Fatigue, Skin irritation

4.3. Indication of any immediate medical attention and special treatment needed
Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
Water mist, Foam, Carbon dioxide (CO2), Extinguishing powder

Unsuitable extinguishing media:
Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Pressurised container: May burst if heated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protection equipment. First aider: Pay attention to self-protection!

6.1.2. For emergency responders

Personal protection equipment:

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clean contaminated articles and floor according to the environmental legislation.

Other information:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Further information on proper storage: see section 7.
For further information on personal protective equipment: see section 8.
For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Wear personal protection equipment (refer to section 8).
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
Avoid contact with eyes and skin.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advices on general occupational hygiene
Avoid exposure - obtain special instructions before use. Wear suitable work clothing. Draw up and observe skin protection programme.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels:
Keep container tightly closed. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:
Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Keep away from food, drink and animal feed.

Storage class (TRGS 510, Germany): 2B – Aerosol dispensers and lighters

Further information on storage conditions:
Protect from frost. Protect from direct sunlight. Store in a cool dry place. The official regulations for the storage of pressurised gas packages must be observed.

7.3. Specific end use(s)
Recommendation:
No further relevant information available.

SECTION 8: Exposure controls/personal protection

*
8.1. Control parameters
8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	**carbon dioxide** CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)
MAK (AT)	**carbon dioxide** CAS No.: 124-38-9 EC No.: 204-696-9	② 10,000 ppm (18,000 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	**carbon dioxide** CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)

8.1.2. Biological limit values
No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	2,035 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	608 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	773 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	300 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

8.2.2. Personal protection equipment

Eye/face protection:

Suitable eye protection: Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:
Use protective skin cream before handling the product. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.
The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Suitable material: NBR (Nitrile rubber)
Breakthrough time: 480 min.
Thickness of the glove material: 0,45 mm
EN ISO 374

Body protection:
Wear suitable work clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
If the relevant occupational exposure limits are exceeded, the following must be observed: Suitable respiratory protective device: Combination filter device (DIN EN 141). Filter unit with filter or blower filter unit type: AX
Observe the wear time limits as specified by the manufacturer.
Observe legal rules and regulations.

8.2.3. Environmental exposure controls

Observe legal rules and regulations.

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol
Colour: colourless
Odour: solvent-like
flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
Initial boiling point and boiling range	88 °C		
Flash point	-12 °C		
Evaporation rate	*No data available*		
Upper/lower flammability or explosive limits	0.6 – 7.2 Vol-%		

Parameter	Value	at °C	① Method ② Remark
Vapour pressure	*No data available*		
Density	0.714 g/cm³	20 °C	① DIN 51757
Water solubility	practically insoluble		
Kinematic viscosity	< 7 mm²/s	40 °C	

9.2. Other information
The data refer to the technical active substance: relative density, colour, odour, viscosity, pH-value.

SECTION 10: Stability and reactivity

10.1. Reactivity
Flammable

10.2. Chemical stability
The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions
Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials
Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products
Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

Further information
Do not mix with other chemicals.

SECTION 11: Toxicological information

*
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6
LD_{50} oral: >5,000 mg/kg (Rat) OECD 401
LD_{50} dermal: >2,920 mg/kg (Rabbit)
LC_{50} Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat) OECD 403
LC_{50} Acute inhalation toxicity (vapour): >25.2 mg/L 4 h (Rat)
carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9
ATE (inhalation, vapour): 259,354 mg/L
LD_{50} oral: ≥5,000 mg/kg (Ratte)
LD_{50} dermal: ≥5,000 mg/kg (Kaninchen)
LC_{50} Acute inhalation toxicity (dust/mist): ≥50 mg/L 4 h (Ratte)

Acute oral toxicity:
Based on available data, the classification criteria are not met.

Acute dermal toxicity:
Based on available data, the classification criteria are not met.

Acute inhalation toxicity:
Based on available data, the classification criteria are not met.

Skin corrosion/irritation:
Causes skin irritation.

Serious eye damage/irritation:
Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity:
Based on available data, the classification criteria are not met.

STOT-single exposure:
May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure:
Based on available data, the classification criteria are not met.

Aspiration hazard:
May be fatal if swallowed and enters airways.

Additional information:
No data available

11.2. Information on other hazards

Endocrine disrupting properties:
None of the ingredients are included.

SECTION 12: Ecological information

*

12.1. Toxicity

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6
LC_{50}: 11.4 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203
EC_{50}: 3 mg/L 2 d (crustaceans, Daphnia magna) OECD 202
NOEC: 0.17 mg/L 21 d (crustaceans, Daphnia magna)
LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)
EC_{50}: 30 – 100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
LC_{50}: >1 – 10 mg/L 4 d (fish, Pimephales promelas)
EC_{50}: >1 – 10 mg/L 2 d (crustaceans, Daphnia magna)
NOEC: 2.045 mg/L 28 d (fish, Oncorhynchus mykiss)
NOEC: 1 mg/L 21 d (crustaceans, Daphnia magna) OECD 211
ErC_{50}: 10 – 30 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201
LOEC: 0.32 mg/L 21 d (Daphnia magna)
LC_{50}: 11.4 mg/L 4 d (fish)

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6
Biodegradation: Yes, rapidly

Additional information:
There are no data available on the mixture itself. AOX (mg/l): 0

12.3. Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6
Log K_{OW}: 5.2
Bioconcentration factor (BCF): 250

Accumulation / Evaluation:
No further relevant information available.

12.4. Mobility in soil
No information available.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane EC No.: 921-024-6	
Results of PBT and vPvB assessment: —	
carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	
Results of PBT and vPvB assessment: —	

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties
This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

*
12.7. Other adverse effects
water hazard class 2: obviously hazardous to water

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

16 05 04 *	Gases in pressure containers (including halons) containing hazardous substances

**: Evidence for disposal must be provided.*

Waste code packaging

15 01 04	metallic packaging

Waste treatment options

Appropriate disposal / Product:
Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane)	AEROSOLS, flammable
* **14.3. Transport hazard class(es)**			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
		 MARINE POLLUTANT	

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.6. Special precautions for user			
Special Provisions: 190 | 327 | 344 | 625 **Limited quantity (LQ):** 1 L **Excepted Quantities (EQ):** E0 **Classification code:** 5F **Tunnel restriction code:** (D) **Remark:** Caution: Flammable liquid!	**Special Provisions:** 190 | 327 | 344 | 625 **Limited quantity (LQ):** 1 L **Excepted Quantities (EQ):** E0 **Classification code:** 5F **Remark:** Caution: Flammable liquid!	**Special Provisions:** 63 | 190 | 277 | 327 | 344 | 381 | 959 **Limited quantity (LQ):** 1000 mL **Excepted Quantities (EQ):** E0 **EmS-No.:** F-D, S-U **Remark:** Caution: Flammable liquid!	**Special Provisions:** A145 | A167 | A802 **Limited quantity (LQ):** Y203 **Excepted Quantities (EQ):** E0 **Remark:** IATA Packing Instructions - Passenger: 203 IATA Maximum Quantity - Passenger: 75 kg IATA-Verpackungsanweisung - Cargo: 203 IATA Maximum Quantity - Cargo: 150 kg Caution: Flammable liquid!

14.7. Maritime transport in bulk according to IMO instruments
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:
Regulation (EC) No 1907/2006 ANNEX XVII
Aerosol Directive (75/324/EEC)

Restrictions on use:
Restrictions on use (REACH, Annex XVII) Entry 3, Entry 40

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:
Volatile organic compounds (VOC) content in percent by weight: 95.7 weight-%

15.1.2. National regulations
No data available

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

3.2.	Mixtures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.7.	Other adverse effects
14.3.	Transport hazard class(es)
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

* 16.2. Abbreviations and acronyms
ACGIH American Conference of Governmental Industrial Hygienists

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AOX	Adsorbable Organic halogen compounds
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC_{50}	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC_{50}	Lethal (fatal) Concentration 50%
LD_{50}	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
ZNS	central nervous system

16.3. Key literature references and sources for data
No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters *(Aerosol 1)*	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard *(Asp. Tox. 1)*	H304: May be fatal if swallowed and enters airways.	
STOT-single exposure *(STOT SE 3)*	H336: May cause drowsiness or dizziness.	
Skin corrosion/irritation *(Skin Irrit. 2)*	H315: Causes skin irritation.	
Hazardous to the aquatic environment *(Aquatic Chronic 2)*	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

Hazard statements	
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice
No data available

16.7. Additional information
To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.